

Low Pass Filter

50Ω DC to 40 MHz

SXLP-40+

Maximum Ratings

Operating Temperature -40°C to 85°C

Storage Temperature -55°C to 100°C

RF Power Input 0.5W Max.

Permanent damage may occur if any of these limits are exceeded.


Pin Connections

INPUT 1

OUTPUT 8

GROUND 2, 3, 4, 5, 6, 7

Outline Drawing




Outline Dimensions (inch mm)

	A	B	C	D	E	F
	.44	.74	.27	.200	.07	.060
	11.18	18.80	6.86	5.08	1.78	1.52
	G	H	J	K	L	M
	.040	.660	.200	.470	.055	.060
	1.02	16.76	5.08	11.94	1.40	1.52
						grams
						3.0

Demo Board MCL P/N: TB-368

Suggested PCB Layout (PL-230)




Features

- high rejection
- sharp cut-off
- shielded package
- aqueous washable
- low cost

Applications

- cable system (video & data)
- defense communications
- receivers / transmitters
- harmonic rejection



CASE STYLE: HF1139

PRICE: \$8.95 ea. QTY (1-9)


+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Low Pass Filter Electrical Specifications (T_{AMB} = 25°C)

PASSBAND (MHz)	f _{co} , MHz Nom.	STOPBAND (MHz)	VSWR (:1)
(Loss < 1dB)	(Loss 3dB)	(Loss > 20dB) (Loss > 40dB)	Passband Typ. Stopband Typ.
DC - 40	50	54 - 80 80 - 2750	1.3 18

Typical Frequency Response






Functional Schematic



Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)	Frequency (MHz)	Group Delay (nSec)
$\bar{x}$	σ			
0.5	0.24	0.01	1.0	19.59
5.0	0.29	0.01	3.0	18.97
25.0	0.42	0.01	5.0	18.91
35.0	0.59	0.02	10.0	19.17
40.0	0.67	0.03	12.0	19.22
49.0	1.89	0.09	15.0	19.77
50.0	3.45	0.29	17.0	19.85
50.4	4.71	0.41	20.0	20.23
51.0	7.08	0.60	22.0	20.83
52.0	12.33	0.83	25.0	21.43
53.0	18.80	0.97	30.0	23.18
54.0	27.01	1.19	35.0	25.45
80.0	47.43	0.45	37.0	26.71
100.0	62.54	0.44	39.0	28.69
200.0	84.33	3.23	40.0	29.68
600.0	86.91	3.37	41.0	31.55
1000.0	84.47	3.62	45.0	41.14
2000.0	62.71	0.64	48.0	58.69
2750.0	47.57	0.24	50.0	88.49



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs & shopping online see web site

REV. OR
M118418
EDR-8893AUF1
SXLP-40+
URJ/RAV
121016
Page 1 of 1