






REV.	DATE	DESCRIPTION
NC	09/05/00	INITIAL RELEASE
A	10/01/06	UPDATE DRAWING FORMAT



RECOMMENDED
MOUNTING HOLE

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex							
8						DRAWN	G.R.S.	10/02/06	PART DESCRIPTION TNC REVERSE POLARITY CRIMP JACK 2 HOLE PANEL (FOR RG-178B/U, 196A/U CABLE)						
7						CHECKED									
6						ISSUED									
5						SHEET	1 OF 1		PART NO. 122459RP						
4	FERRULE	COPPER	NICKEL	1											
3	CONTACT PIN	PHOS. BRONZE	GOLD	1					DWG. NO. 122459RP.DWG REV. A SIZE A SCALE NA						
2	INSULATOR	TEFLON	NATURAL	1											
1	BODY	BRASS	NICKEL	1											
	DESCRIPTION	MATERIAL	FINISH	QTY				CAD FILE C:/122/122459RP.DWG							