

50 Ohm N Male to 75 Ohm N Female Adapter



TECHNICAL DATA SHEET

PE9349

50 Ohm N Male to 75 Ohm N Female Adapter

Configuration

Connector 1N MaleImpedance 150 OhmsConnector 2N FemaleImpedance 275 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +165

Size

Length, in [mm] 1.383 [35.13] Width/Dia., in [mm] 0.8 [20.32]

Connector 1

Type N Male
Inner Conductor Material and Plating Silver
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Connector 2

Type N Female
Inner Conductor Material and Plating Silver
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/n-male-n-female-straight-adapter-pe9349-p.aspx

50 Ohm N Male to 75 Ohm N Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9349 CAD Drawing 50 Ohm N Male to 75 Ohm N Female Adapter

