SA13-24V/207



Sector Antenna

The most important thing we build is trust


Designed for Commercial Applications

Suitable for Multiple Applications


Vertical Polarisation

Low Profile

Compact







Elevation Pattern

	80.50 [3.17] *MOUNTE 4 OFF M4 TAPPED H	D VIA x 6 OLES
77.80 [3.06	2.35 [0.09]	0
320 [12.60] 312 [12.28]	*2 MOUNTING OPTIONS	G
SIDE VIEW V V	N(F) CONNECTOR	
63.60 [2.50]	23.60 [0.93]	
BASE VIEW GA: 0207	88 [3.46]	*MOUNTED VIA M4 U-BOLTS THRO' 4 OFF Ø 4.5 HOLES

ELECTRICAL		
Frequency	2.35 - 2.55 GHz	
Gain	13 dBi Nom	
Polarisation	Linear (Vertical)	
Beamwidth	80° (Az) x 20° (EI) Approx	
Cross Polar	20 dB Typ	
VSWR	1.5:1 Max	
Power Rating	10 W	
Front to Back	30 dB	
MECHANICAL		
Standard Finish	Gloss White	
Mass	465g (16.4 oz)	
Temperature	-20° to +50°C	
Wind Loading	4.5 Kg (10.0 lbs) @ 100mph	
MOUNTING OPTIONS		

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 231210

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com