



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9887
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4043-003

2 - 30 MHz
1000 WATTS
LINEAR POWER RF AMPLIFIER

Solid State Band-specific High Power RF Amplifier

The 4043-003 is a 1000 Watt band-specific amplifier that covers the 2 – 30 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4043-003 comes with an extended multiyear warranty.

	Parameter	Specification @ 25 °C
Electrical		
1	Frequency Range	2 – 30 MHz
2	Saturated Output Power	1000 Watts typical
3	Rated Output Power	500 Watts min
4	Small Signal Gain	+47 dB min
5	Small Signal Gain Flatness	± 2.0 dB max
6	IP ₃	+63 dBm typical
7	Harmonics @ Rated Power, 500 Watts	< -10 dBc for in-band range < -20 dBc for out-of-band range
8	Spurious Signals	< -60 dBc @ 500 Watts
9	Input/Output VSWR	3:1 nominal
10	Load VSWR @ Rated Power	Infinite phase and amplitude
11	Input/Output Impedance	50 Ohms nominal
12	AC Input @ Rated Power AC Input @ Saturated Power	1.6 KW typ 2400 KW
13	AC Input	208 ± 10% VAC, single phase
14	RF Input	+10 dBm for Rated Power
15	RF Input Overdrive	+13 dBm max
16	Class of Operation	AB
Mechanical		
17	Dimensions	19" x 8.75" x 20"
18	Weight	76 lb.
19	Connectors	Type-N
20	Grounding	Chassis
21	Cooling	Internal Forced Air
Environmental		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	See DWG NO. 2062AS167

CIRCUIT PROTECTIONS

- ◇ Thermal Overload @ 85 °C
- ◇ Over Current
- ◇ Over Voltage

ORDERING MODELS

- ◇ FE - F model w/Control Option
- ◇ FT - FE model w/Ethernet Interface



FE Model Shown