



Directional 6 dB SMA Coupler From 1 GHz to 4 GHz Rated To 50 Watts

TECHNICAL DATA SHEET

PE2209-6

Configuration

Connector 1	SMA Female
Connector 2	SMA Female
Coupled Connectors	SMA Female
Design	Directional Coupler

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	1		4	GHz
Directivity	23			dB
Impedance		50		Ohms
Insertion Loss			2	dB
Input Power			50	Watts
Input VSWR			1.2:1	
Secondary Line VSWR			1.2:1	
Peak Power			3	KWatts
Coupling Value		6		dB
Coupling Tolerance			± 1	dB
Coupling Flatness			± 0.5	dB

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size	
Length	3.65 in [92.71 mm]
Width/Dia.	0.38 in [9.65 mm]
Height	1.18 in [29.97 mm]

Connectors

Description	Connector 1	Connector 2	Coupled Connectors
Type	SMA Female	SMA Female	SMA Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	
REACH Compliant	06/18/2012

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 6 dB SMA Coupler From 1 GHz to 4 GHz Rated To 50 Watts PE2209-6](#)



Directional 6 dB SMA Coupler From 1 GHz
to 4 GHz Rated To 50 Watts

TECHNICAL DATA SHEET

PE2209-6

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Directional 6 dB SMA Coupler From 1 GHz to 4 GHz Rated To 50 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 6 dB SMA Coupler From 1 GHz to 4 GHz Rated To 50 Watts PE2209-6](http://www.pasternack.com/directional-6-db-sma-coupler-1-4-ghz-50-watts-pe2209-6-p.aspx)

URL: <http://www.pasternack.com/directional-6-db-sma-coupler-1-4-ghz-50-watts-pe2209-6-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Directional 6 dB SMA Coupler From 1 GHz to 4 GHz Rated To 50 Watts

Directional 6 dB SMA Coupler From 1 GHz to 4 GHz Rated To 50 Watts



NOTES:

- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE2209-6

FSCM NO. 53919

CAD FILE 092908-A

SCALE N/A

SIZE A

XXXX



PASTERNAK®

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com