

1700 MHz < Fo < 2200 MHz

Band Pass

Slopes 70 MHz

Bandwidth 100 MHz


WBCJV10-__

Attenuation 70 dB



Specifications

Passband:	__ (Fo) ± 50 MHz = __ to __ MHz
Passband Insertion Loss:	1.25 dB max. at Fo (2 dB max. at corners)
Passband Return Loss:	14 dB min. (VSWR 1.5:1 max.)
Stopband:	DC to __ MHz and __ to __ MHz
Stopband Attenuation:	70 dB min.
Operating Temperature:	15 °C to 45 °C
Power Handling:	will be quoted (<i>Please see our warranty in this regard</i>)
Dimensions (L x W x H):	max. 205 x 20 x 60 mm (plus connectors and flanges)
Approx. Weight:	0.55 kg
Mounting Provision:	7.5 mm flanges on both ends with 3.3 mm holes
Connector 1:	- Please choose -
Connector 2:	- Please choose -

Typical Performance



10 Section Cavity Design



Connector Options

SMA Female
SMA Male
N Female
N Male
BNC Female
BNC Male

Euro Prices

(USD Prices will be quoted for US-based customers only)

1 - 4 pcs:	€ 1075
5 - 9 pcs:	€ 994
10 - 24 pcs:	€ 920

Delivery Terms

FCA Andechs (free carrier) according to **Incoterms 2010**
In Deutschland liefern wir frachtfrei gemäß CPT **Incoterms 2010** (unversichert).
Regarding payment terms and warranty see [Terms and Conditions](#).
Delivery time: normally 3 to 4 weeks - depending on quantity ordered and on our work load.

Customer is responsible for observing all applicable export laws in regard to filter application and location of end user



Wainwright Instruments GmbH
www.wainwright-filters.com

Tel: +49 8152 918230
Fax: +49 8152 918255
info@wainwright-filters.com