

MECHANICAL SPECIFICATIONS

PRODUCTION
RELEASE

NOTE:
THIS DRAWING INCORPORATES
THIRD ANGLE PROJECTION
INTERPRET IN ACC. WITH Y14.5-1993

REVISIONS

REV	DESCRIPTION	APPROVED
D	REVISED VSWR & DIAMETER	01/14/2010 D. Saunders

INTERFACE MATES / COMPLY WITH MIL-STD-348 FOR TYPE N

MATERIALS (ALL PER MIL-PRF-39012 & MIL-DTL-39030)

INNER CONDUCTOR:

BERYLLIUM COPPER PER ASTM B196 & B197, GOLD
PLATED FINISH PER MIL-PRF-39012

OUTER CONDUCTOR/NUT/CHAIN EYELETS:

STAINLESS STEEL, CORROSION RESISTANT PER
ASTM A484 & A582, CLASS 303, COND. A.,
PASSIVATED SS FINISH

DIELECTRIC: TEFLON PER ASTM D1710.

FOR UNMARKED UNITS OR FOR CUSTOM MARKING CONTACT FACTORY FOR
PART NUMBER / SUFFIX TO APPEND TO MODEL NUMBER

MEETS ALL ENVIRONMENTAL REQUIREMENTS IN MIL-DTL-39030

ELECTRICAL SPECIFICATIONS

Frequency Range

3001-6120-02	DC - 18 GHz
3001-6121-02	DC - 12.4 GHz
3001-6124-02	DC - 18 GHz*
3001-6125-02	DC - 12.4 GHz*

* = COMES WITH OPT. CHAIN SHOWN


VSWR:	DC - 4 GHz	1.10:1
	4 - 8 GHz	1.15:1
	8 - 12.4GHz	1.20:1
	12.4 - 18GHz	1.25:1

IMPEDANCE 50 OHMS

TEMPERATURE RANGE (°C) -65 TO +125 OPERATING
+150° STORAGE

POWER (AVG) 2 WATTS**
POWER (PEAK) (<5 μ SEC. PW, <0.05% DUTY CYCLE) 500 WATTS

**POWER DERATES LINEARLY FROM +25°C TO <10 ° @ +125°C CASE



DRAWING PRACTICES PER ASME-Y-14.5
MIL-STD-100 & 1000

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND
APPLY BEFORE/ AFTER PROCESSING

SURFACE
ROUGHNESS

FINISH
SEE NOTES

MATERIAL
SEE NOTES

UNLESS OTHERWISE SPECIFIED
TOLERANCES IN

DECIMALS	INCH	MIL
.X"	.05"	[1.3]
.XX"	.030"	[.76]
.XXX"	.015	[.39]
.XXXX"	.0005"	[.013]

ANGLES ±

UNLESS OTHERWISE NOTED
DIAS CONCENTRIC <.003 T.I.R.

DRAWN
D. SAUNDERS

CHECKED
D. SAUNDERS

DATE
01/14/2010

DATE
01/14/2010

THESE DRAWINGS AND SPECIFICATIONS ARE
THE PROPERTY OF XMA CORP. / OMNI
SPECTRA AND SHALL NOT BE REPRODUCED,
COPIED, NOR USED - IN WHOLE OR IN PART -
AS A BASIS FOR THE DESIGN, MANUFACTURE
OR SALE OF OTHER ITEMS WITHOUT THE
EXPRESS WRITTEN PERMISSION OF XMA
CORP. CUSTOMERS AND VENDORS MAY
COPY FOR INTERNAL REVIEW USE AS NEEDED

WWW.XMACorp.com Sales@XMACorp.com
XMA Powered by: **Omni**
Spectra®

XMA Corp. 150 Dow St. Manchester, NH 03045 (603) 222-2256 fax 222-2259

TITLE
2 WATT TYPE N TERMINATION
18 GHz

SIZE	CAGE CODE	DWG NO.
C	3HT76	3001-612X-02

SCALE	PLATING AREA	XXX	SHEET 1 OF 1
5 : 1	SOLDER - INCHES		