


T50R0-1000-6X Features:


- Flange Mount
- RoHS Compliant
- Customer Defined Testing Available
- High Rated Power
- Covered Resistor Element (First Chip)
- $\pm 5\%$ Resistor Tolerance

T50R0-1000-6X Parameters:


Operating Frequency:	DC - 4.5GHz
Rated Power:	1000W*
Return Loss (Typical)**:	20dB or Better (DC - 2.5GHz) 17dB or Better (>2.5GHz - 4.5GHz)
Impedance:	50 Ω $\pm 5\%$ ***
Resistor Construction:	Thick Film on BeO
Flange Construction:	Silver Plated Copper
Lead Construction:	Silver Plated Copper
Operating Temperature:	-55 to +150°C



T50R0-1000-6X Dimensions:



T50R0-1000-6X Power Derating Curve



Dimensions in inches [mm]
Tolerance is ± 0.010 [0.254]
unless otherwise stated



* Rating based on $\leq 100^\circ\text{C}$ constant flange temperature
 ** In a matched, continuous 50 Ω system with proper workmanship
 *** Other values and tolerances available. Contact factory.

Ordering Information:

T 50R0 - 1000 - 6X			
Prefix for Flanged Termination	Value Code 50R0 - 50 Ω	Rated Power 1000 - 1000W	Assigned by Factory

Barry Industries reserves the right to change part number and/or process without notification.



T50R0-1000-6X Reliability Data:

Parameter:	Test Condition:	Results:
Short Time Overload	Apply 1.1x Rated Power for 5 Seconds.	± 5.0% Resistance Shift
Rated Load Life	Apply 1/2 Power Under 40°C ±2°C 90 Minutes on/ 30 Minutes off. Repeat for 100 hours	± 5.0% Resistance Shift
Moisture Resistance	MIL-PRF-55342 para.4.8.9 95% RH, 25°C - 65°C	± 5.0% Resistance Shift
Resistance to Soldering Heat (Lead)	MIL-STD-202 Method 210 Test Condition "A"	± 5.0% Resistance Shift
Resistance to Soldering Heat (Assembly)	MIL-STD-202 Method 210 Test Condition "J"	± 5.0% Resistance Shift
Terminal Strength	MIL-STD-202 Method 211 Test Condition "A" 3lbs. Test Condition "B" 5 bends	No Significant Abnormality (Visual)
Solderability (Lead only)	MIL-STD-202 Method 208 Test C	>95% Covered
High Temperature Storage	125°C ±2°C for 500 Hours	1.) ± 5.0% Resistance Shift 2.) No Significant Abnormality (Visual)
Thermal Shock	-5°C to +150°C 30 Minutes Dwell, 5 Cycles	1.) ± 5.0% Resistance Shift 2.) No Significant Abnormality (Visual)

