


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

FREQUENCY RANGE: 1–3 GHz
 INSERTION LOSS: 1.6dB Max. (1.5dB Max. Reflective)
 ISOLATION: 60dB Min.
 VSWR: 1.60:1 Max.
 INPUT POWER: 200 mW (23 dBm)
 SWITCHING TIME: 100 nSEC



Driver Schottky TTL
 Voltage/Current Required:
 +5 Vdc @ +120 mA, Typical
 -5 Vdc @ -50 mA, Typical
 Higher speeds available.
 Individual TTL Control Logic:
 "0" (-0.3V to +0.8V) = ON
 "0" (+2.0V to +5.0V) = OFF

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A SHEET: N/A	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .02 \pm .008$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: SP8T PIN DIODE SWITCHES					
DRAWN: Paiboon Luekhamhan DATE: 12-18-2009		PART NO. D8-6					
APPROVED: T. Nguyen DATE: 12-18-2009		CAGE CODE: OD2L5		SIZE: A REV: N/A		DWG NO. 84018	
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		DO NOT SCALE THE DRAWING					