



Features

- For WiBro and WiMAX applications
- Usable bandwidth 10 MHz
- High attenuation
- Balanced operation 200 Ω
- Ceramic Surface Mount Package (SMP)
- Hermetic
- RoHS compliant (2002/95/EC), Pb-free 




Package

Surface Mount 7.00 x 5.50 x 1.24 mm



Pin Configuration

Bottom View



Pin No.	Description
9	Input
10	Input return
4	Output
5	Output return
1,2,3	Case ground
6,7,8	Case ground

Dimensions shown are nominal in millimeters
All tolerances are ± 0.15 mm except overall
length and width ± 0.13 mm

Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m,
over a 2 - 6 μ m Ni plating

Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ -20 to +60 °C


Parameter ⁽³⁾	Minimum	Typical	Maximum	Unit
Center Frequency, f_0	-	456	-	MHz
Minimum Insertion Loss 451 - 461 MHz	-	8.30	9.50	dB
Amplitude Variation 451 - 461 MHz	-	0.45	1.00	dB
30 dB Bandwidth ⁽³⁾	-	20.00	20.35	MHz
Relative Attenuation ⁽³⁾				
10 - 256 MHz	45	70	-	dB
256 - 360 MHz	40	65	-	dB
360 - 421 MHz	45	50	-	dB
421 - 440 MHz	37	40	-	dB
472.4 - 491 MHz	39	42	-	dB
491 - 552 MHz	45	50	-	dB
552 - 656 MHz	40	55	-	dB
656 - 946 MHz	45	60	-	dB
Absolute Group Delay at F_0	-	0.49	0.51	μsec
Group Delay Variation 451 - 461 MHz	-	30	65	ns
Input/Output Return Loss 451 - 461 MHz	9	14	-	dB
Source Impedance (Balanced) ⁽⁴⁾	-	200	-	Ω
Load Impedance (Balanced) ⁽⁴⁾	-	200	-	Ω

Notes:

1. All specifications are based on the test circuit shown below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Referenced to minimum insertion loss
4. This is the optimum impedance in order to achieve performance shown

Test Circuit:

Actual matching values may vary due to PCB layout and parasitics



Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ -40 to +85 °C


Parameter ⁽³⁾	Minimum	Typical	Maximum	Unit
Center Frequency, f_0	-	456	-	MHz
Minimum Insertion Loss 451 - 461 MHz	-	8.30	9.75	dB
Amplitude Variation 451 - 461 MHz	-	0.45	1.25	dB
30 dB Bandwidth ⁽³⁾	-	20.00	20.38	MHz
Relative Attenuation ⁽³⁾				
10 - 256 MHz	45	70	-	dB
256 - 360 MHz	40	65	-	dB
360 - 421 MHz	45	50	-	dB
421 - 440 MHz	37	40	-	dB
472.4 - 491 MHz	39	42	-	dB
491 - 552 MHz	45	50	-	dB
552 - 656 MHz	40	55	-	dB
656 - 946 MHz	45	60	-	dB
Absolute Group Delay at F_0	-	0.49	0.51	μsec
Group Delay Variation 451 - 461 MHz	-	30	75	ns
Input/Output Return Loss 451 - 461 MHz	8	14	-	dB
Source Impedance (Balanced) ⁽⁴⁾	-	200	-	Ω
Load Impedance (Balanced) ⁽⁴⁾	-	200	-	Ω

Notes:







1. All specifications are based on the test circuit shown below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Referenced to minimum insertion loss
4. This is the optimum impedance in order to achieve performance shown

Test Circuit:


Actual matching values may vary due to PCB layout and parasitics



Typical Performance (at +25°C)




Actual matching values may vary due to PCB layout and parasitics



PCB Footprint





The date code consists of: day of the current year (Julian, 3 digits), last digit of the year (1 digit) and hour (2 digits)



This footprint represents a recommendation only
Dimensions shown are nominal in millimeters

Tape and Reel



Dimensions shown are nominal in millimeters
Packaging quantity: 3000 units/reel

Maximum Ratings

Parameter	Symbol	Minimum	Maximum	Unit
Operating Temperature Range	T	-40	+85	°C
Storage Temperature Range	T _{stg}	-40	+85	°C

Important Notes

Warnings

- Electrostatic Sensitive Device (ESD)
- Avoid ultrasonic exposure



RoHS Compliance

- This product complies with EU directive 2002/95/EC (RoHS)



Solderability

- Compatible with JEDEC J-STD-020C Pb-free process, **260°C** peak reflow temperature ([see soldering profile](#))

Links to Additional Technical Information

[PCB Layout Tips](#)

[Qualification Flowchart](#)

[Soldering Profile](#)

[S-Parameters](#)

[RoHS Information](#)

[Other Technical Information](#)

TriQuint's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. TriQuint does not accept any liability for applications, processes, circuits or assemblies, which are implemented using any TriQuint component described in this data sheet.

Contact Information



PO Box 609501
Orlando, FL 32860-9501
USA

Phone: +1 (407) 886-8860
Fax: +1 (407) 886-7061
Email: info-product@tqs.com
Web: www.triquint.com

Or contact one of our worldwide
Network of [sales offices](#),
[Representatives or distributors](#)