


Uncontrolled Drawing



Type SMA male

Type SMA male

Specification:

1. Model: TC26-01-01-600C
2. Nominal Impedance: 50Ω
3. Frequency Range: DC-26.5GHz
4. VSWR: 1.10@DC-6GHz, 1.20@6-13GHz, 1.25@13-18GHz, 1.35@18-26.5GHz
5. Insertion Loss: 0.36dB@DC-1GHz, 0.54dB@1-3GHz, 0.69dB@3-6GHz, 0.93dB@6-13GHz, 1.08dB@13-18GHz, 1.44dB@18-26.5GHz
6. Power Capacity(sea level 25°C ambient temperature): 1200W@0.4GHz, 720W@1GHz, 400W@3GHz, 310W@5GHz, 220W@10GHz, 120W@18GHz, 90W@26.5GHz
7. Min. One Time Bend Radius: 25.4mm
8. Phase stability vs Flexure: ±0.25°/GHz; 360 degree bend, 38mm radius
9. Temperature Range: -55°C~+165°C
10. Connector: SMAm-SMAm, Stainless Steel
11. Length: 0.6m

参量项目	数量	规格/名称、单位、材料标准等	图号	505.1506
设计	DESIGNED_	SHJ	文件名称	FILENAME
校对	CHECKED_	ZH	日期	11/7/5
审核 - 日期	APPROVED_		版数	1.1

**BXT** Technologies  
 BXT Technologies  
 Tel:0591-83789500  
 www.bxt-technologies.cn

Microwave Test Cable Assembly  
 TC26-01-01-600C

版数 EDITION  
 图号 SHEET