


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 2–3 GHz
Isolation: 20dB Min.
Insertion loss: 0.50dB Max.
VSWR: 1.25:1 Max.
Operating Temperature: 0°C to +55°C

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
DRAWN: Paiboon Luekhamhan		DATE: 08-22-2011		DRAWING TITLE: COAXIAL CIRCULATOR	
				PART NO.: CS-42	
APPROVED: T. Nguyen		DATE: 08-22-2011		CAGE CODE: OD2L5	
				SIZE: N/A REV: B DWG NO.: 84877	
PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)				DO NOT SCALE THE DRAWING	