

Plug-In Frequency Mixer

Level 10 (LO Power +10 dBm) 0.05 to 2000 MHz

Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

LO	8
RF	1
IF	3
GROUND	2,5,6,7
CASE GROUND	2,5,6,7
NOT USED	4

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	H	J	K	wt	
.200	.20	.14	.031	grams	
5.08	5.08	3.56	0.79	5.2	


Features

- wideband, 0.05 to 2000 MHz
- low conversion loss, 5.59 dB typ.
- high L-R isolation, L-I isolation, 40 dB typ.
- hermetic, metal case

Applications

- GPS
- cellular
- defense & aeronautical systems
- military, hi-rel applications

SRA-220+



CASE STYLE: A01
PRICE: \$36.20 ea. QTY (1-9)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)					
LO/RF f_L - f_U	IF	Mid-Band m		Total Range Max.		L		M		U		L		M		U	
		$\bar{X}$	σ	Max.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.
0.05-2000	.05-500	5.59	.11	8.0	9.0	25	20	40	30	30	20	25	20	40	30	25	15


1 dB COMP.: +5 dBm typ.

L = low range [f_L to $10 f_L$]
m = mid band [$2 f_L$ to $f_U/2$]
M = mid range [$10 f_L$ to $f_U/2$]
U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm
0.05	30.05	6.31	20.56	20.32	1.42	1.38
1.00	31.00	5.23	37.02	35.22	1.42	1.38
5.00	35.00	5.34	41.42	40.80	1.44	1.34
20.00	50.00	5.57	42.73	42.42	1.45	1.41
50.00	80.00	5.59	42.75	42.09	1.44	1.37
100.00	70.00	5.50	42.49	40.87	1.49	1.34
153.89	123.89	5.49	42.03	38.92	1.63	1.30
230.81	200.81	5.78	41.75	36.48	2.03	1.24
307.73	277.73	5.75	41.49	34.62	2.73	1.22
500.00	470.00	5.97	38.13	32.70	3.06	1.24
615.42	585.42	6.37	40.61	34.50	3.23	1.30
692.34	662.34	6.90	42.63	35.22	3.35	1.25
846.18	816.12	7.39	40.51	34.89	2.98	1.34
1076.90	1047.20	7.31	36.30	27.82	2.40	1.38
1230.80	1200.80	6.91	32.05	23.22	1.60	1.36
1307.70	1277.80	6.81	30.96	21.56	1.20	1.31
1461.50	1431.70	7.49	24.40	19.73	1.04	1.35
1615.40	1585.50	7.29	34.31	19.71	1.19	1.37
1769.20	1739.20	7.80	38.84	18.84	1.31	1.43
2000.00	1970.30	8.89	31.97	19.56	1.41	1.56

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine **Mini-Circuits** Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M98898
SRA-220
DJ/TD/CP/AM
130502
Page 1 of 2

