


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS:

Frequency Range: 14.5–15.5 GHz

Isolation: 20dB Min.

Insertion loss: 0.5dB Max.

VSWR: 1.25:1 Max.

Operating Temperature: –54°C to +85°C

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.02 \pm 0.010$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: COAXIAL ISOLATOR
DRAWN: Paiboon Luekhamhan	DATE: 08-17-2011	PART NO. IS-149		
APPROVED: T. Nguyen	DATE: 08-17-2011	CAGE CODE: OD2L5	SIZE: A	REV: N/A
THIRD ANGLE PROJECTION 		DWG NO. 85837		
		DO NOT SCALE THE DRAWING		