



剥线尺寸
stripping dimension



产品型号 type	电缆型号 cable type
N-KY3Y	SFT-50-1.5-1、SYV-50-2-1、RG316/U、RG179B/U

Electrical Characteristics:

- Characteristic Impedance: 50Ω
- Frequency range: DC~4Ghz
- Contact resistance
Center conductor: $\leq 1.0\text{ m}\Omega$
Out conductor: $\leq 0.2\text{ m}\Omega$
- Insulation resistance: $\geq 5000\text{ M}\Omega$
- Insulator withstanding: 1500V
- VSWR: ≤ 1.4
- Durability: 500cycles

主要性能指标:

- 特性阻抗: 50Ω
- 频率范围: DC~4Ghz
- 接触电阻:
中心导体: $\leq 1.0\text{ m}\Omega$
外导体: $\leq 0.2\text{ m}\Omega$
- 绝缘电阻: $\geq 5000\text{ M}\Omega$
- 介质耐压: 1500V
- 电压驻波比: ≤ 1.4
- 插拔次数: 500次

Application: MIL-C-39012/1E

执行标准: MIL-C-39012/1E

Material&Finishing

- Center contact :
Female: phosphor bronze, gold plated
- Bodies: brass, nickel plated
- Crimp ferrule: copper, nickel plated
- Insulators: PTFE

材料和镀层

- 中心接触件:
插孔: 锡磷青铜, 镀金
- 壳体: 黄铜, 镀镍
- 线夹: 黄铜, 镀镍
- 绝缘子: 聚四氟乙烯

		SCALE	
		1.5:1	
	NAME	DATE	
DRAWN			
CHECKED			
APPROVED			

N-KY3Y
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE mm, TOLERANCES ARE
FRACTIONS DECIMALS ANGLES
.X± .15 ±1°
.XX± .05
.XXX±

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.