

Product Features

- Mini Tri-Band Rubber Duck Antenna
- 2400-2480 MHz & 4900-5300 MHz & 5725-5850 MHz Freq Bands
- 2dBi Omni Radiation Pattern

Description

The PE51095 swivel style Mini Tri Band Rubber Duck Dual Band Antenna provides excellent performance in multiple wireless applications. Its small size and rugged construction is perfect for both indoor and portable wireless systems.

Specifications ⁽¹⁾

Parameter	Value	Units	Description
Band 1 Frequency	2400-2480	MHz	
Band 2 Frequency	4900-5300	MHz	
Band 2 Frequency	5725-5850	MHz	
Impedance	50	Ohms	
Gain	2	dBi	Max
Polarization	O	Omni	
RF Power Rating	50	W	Max
Maximum VSWR	<2.3	ratio	Between Min and Max Freq
Length	195	mm	7.6 inches
Connector Type		RP-SMA(M)	Swivel Style SMA
Operating Temperature	-40-60	Deg C	



Ordering Information

Part Number	Description
PE51095	2400-2480 and 4900-5300 and 5725-5850 MHz Tri Band Rubber Duck, RP-SMA(M)

(1) Pasternack reserves the right to change specifications or information without notice.

(2) All Specifications "Typical" values