

75 Ohm SMC Jack Bulkhead Connector Crimp/Solder Attachment For RG179, RG187, .177 inch D Hole



TECHNICAL DATA SHEET

PE4256

75 Ohm SMC Jack Bulkhead Connector Crimp/Solder Attachment For RG179, RG187, .177 inch D Hole

Configuration

Connector SMC Jack
Connector Interface Type RG179,RG187
Cable Attachment Method (Shield/Contact) Crimp/Solder
Body Style Straight
Mount Method Bulkhead

Electrical Specifications

Frequency Range, GHz

Impedance, Ohms

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

Dielectric Voltage, Vrms

Dielectric Voltage, Vrms

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 0.953 [24.21]

 Width/Dia., in [mm]
 0.43 [11]

 Weight, lbs [g]
 0.013 [5.9]

Connector

Type SMC Jack
Contact Material and Plating Gold
Body Material and Plating Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/smc-jack-standard-rg179-rg187-connector-pe4256-p.aspx

75 Ohm SMC Jack Bulkhead Connector Crimp/Solder Attachment For RG179, RG187, .177 inch D Hole from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE4256 CAD Drawing

75 Ohm SMC Jack Bulkhead Connector Crimp/Solder Attachment For RG179, RG187, .177 inch D Hole

