


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 14–14.5 GHz
 Insertion Loss: 1.0dB Max.
 Isolation: 17dB Min.
 VSWR In/Out: 1.50:1/1.40:1 Max.
 Amplitude Balance: ± 0.4 dB Max.
 Phase Balance: ± 7 Deg. Max.
 Power: 30W (vswr@1.2)

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWN: Paiboon Luekhamhan		DATE: 06-16-1999		DRAWING TITLE: 4-WAY POWER DIVIDER PART NO. PS4-28
APPROVED: T. Nguyen		DATE: 06-16-1999		
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5 SIZE: A REV: N/A DO NOT SCALE THE DRAWING		DWG NO. 80185