

## N Female Bulkhead Connector Crimp/Solder Attachment For PE-C400, 0.400 inch, .640 inch DD Hole



## TECHNICAL DATA SHEET

PE44530

N Female Bulkhead Connector Crimp/Solder Attachment For PE-C400, 0.400 inch, .640 inch DD Hole

Configuration

Connector N Female
Connector Specification MIL-STD-348A
Connector Interface Type PE-C400,0.400 inch
Cable Attachment Method (Shield/Contact) Crimp/Solder

Body Style Straight
Mount Method Bulkhead

**Electrical Specifications** 

Frequency Range, GHz
Impedance, Ohms
Maximum Operating Voltage, Volts
DC to 11
50
1,500

Frequency 1

Frequency, GHz DC to 6 VSWR 1.3:1

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.72 [43.69]

 Width/Dia., in [mm]
 0.87 [22]

 Weight, lbs [g]
 0.096 [43.54]

Connector

Type N Female
Contact Material and Plating Brass, Gold
Body Material and Plating Brass, Tri-Metal

Dielectric Type Teflo

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/n-female-standard-pe-c400-0.400-connector-pe44530-p.aspx

N Female Bulkhead Connector Crimp/Solder Attachment For PE-C400, 0.400 inch, .640 inch DD Hole from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

## PE44530 CAD Drawing

N Female Bulkhead Connector Crimp/Solder Attachment For PE-C400, 0.400 inch, .640 inch DD Hole

