

4

3

2

1

MECHANICAL

CONTACT: BREAK BEFORE MAKE

ACTUATOR: LATCHING

SWITCHING SPEED: 20 mSEC MAX

ELECTRICAL

ACTUATOR VOLTAGE: 28.0 Vdc (22.0–32.0 Vdc)

ACTUATOR CURRENT: 0.500 A MAX @ 28.0 Vdc

POWER HANDLING: 200 WCW @ 1.0 GHz

IMPEDANCE: 50 OHMS

ENVIRONMENTAL

OPERATING TEMP: -54°C to +90°C

SINE VIBRATION: 30 G'S rms

LIFE : 1,000,000 CYCLES

RANDOM VIBRATION: 20 G'S rms

SPECIFICATION:


FREQUENCY RANGE (GHz): DC–2.0 2.0–4.0 4.0–8.0 8.0–12.4 12.4–18.0

VSWR (Max.): 1.20:1 1.25:1 1.30:1 1.40:1 1.50:1

INSERTION LOSS (dB): 0.20 0.25 0.30 0.40 0.50

ISOLATION (dB): 90 80 80 70 60

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		SHEET: N/A
DRAWN: Paiboon Luekhamhan		DATE: 02-24-2009		DRAWING TITLE: ELECTROMECHANICAL SWITCHES
APPROVED: T. Nguyen		DATE: 02-24-2009		
		PART NO. E5-7-LIS/28P		CAGE CODE: OD2L5
		SIZE: N/A		
		REV: N/A		DWG NO. 84192
		DO NOT SCALE THE DRAWING		