

ADS-VNAPC8PC3

Ruggedized NMD 3.5 Jack
To 3.5 Plug

50Ω

Technical drawing of the NMD 3.5 Jack assembly. The drawing shows a side view of the assembly with the following dimensions and labels:

- Overall diameter: $\varnothing 22$ ($\varnothing .866$)
- Threaded section: $11/16-24UNEF-2B$
- Threaded section: $1/4-36UNS-2A$
- Length of threaded section: 17.8 ($.701$)
- Overall length: 34.3 REF. (1.350 REF.)
- Hex nut: HEX 19 ($.748$)
- Across flats: ACROSS FLATS 7 ($.276$)
- Hex nut: 8 HEX ($.315$ HEX)

Note: NMD 3.5 Jack to be mounted directly on vector network analyser.

Parts	Material	Plating (Micro-inch)
Retainer Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Gasket	Silicon	
Wave Washer	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Ferrule	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Holder	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Contact Pin	Beryllium Copper	Gold 20 Over Nickel 50 Over Copper 20
Insulator	NORYL	
Body	Stainless Steel	Passivated
Coupling Nut	Stainless Steel	Passivated

Weight:

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.