

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)577-9887 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5062

1 - 1000 MHz **100 WATTS**

Solid State Broadband High Power RF Amplifier

The 5062 is a 100 Watt broadband amplifier covers the 1 - 1000 MHz frequency range. This small lightweight amplifier and utilizes Class A/AB linear power devices that provide 3rd excellent order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5062 comes with an extended multiyear

	<u>Parameter</u>	Specification @ 25° C
Electrical		
1	Frequency Range	1 – 1000 MHz
2	Saturated Output Power	100 Watts typical
3	Power Output @ 1dB Comp.	80 Watts typ
4	Small Signal Gain	+50 dB min
5	Gain Flatness / with ALC	<u>+</u> 2.0 / <u>+</u> 0.75 dB max
6	IP ₃	+54 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 60 Watts
9	Spurious Signals	> -60 dBc typical @ 60 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	2500 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	0 dBm
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<u>Mechanical</u>		
16	Dimensions	19" x 8.75" x 20"
17	Weight	80 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
<u>Environmental</u>		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport Specifications subject to change without notice.

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

ORDERING MODELS

- ♦ R Rear Panel Connectors
- ◊ F Front Panel Connectors
- ♦ RE Rear Panel Connectors and Control Option
- ♦ FE Front Panel Connectors and Control Option

