

# Surface Mount Directional Coupler

75Ω 20 to 1000 MHz


## Maximum Ratings

|                                                                 |                |
|-----------------------------------------------------------------|----------------|
| Operating Temperature                                           | -40°C to 85°C  |
| Storage Temperature                                             | -55°C to 100°C |
| Permanent damage may occur if any of these limits are exceeded. |                |


## Pin Connections

|                      |   |
|----------------------|---|
| INPUT                | 1 |
| OUTPUT               | 6 |
| COUPLED              | 3 |
| GROUND               | 2 |
| 75Ω TERM EXTERNAL    | 4 |
| ISOLATE (DO NOT USE) | 5 |

## Outline Drawing




### PCB Land Pattern



## Outline Dimensions (inch/mm)

| A    | B    | C    | D    | E    | F    | G     |
|------|------|------|------|------|------|-------|
| .272 | .310 | .220 | .100 | .112 | .055 | .100  |
| 6.91 | 7.87 | 5.59 | 2.54 | 2.84 | 1.40 | 2.54  |
| H    | J    | K    | L    |      |      | wt    |
| .030 | .026 | .065 | .300 |      |      | grams |
| 0.76 | 0.66 | 1.65 | 7.62 |      |      | 0.20  |

## Demo Board MCL P/N: TB-08 Suggested PCB Layout (PL-042)



- NOTES:
1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
  2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
  3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
  4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

## Features

- wideband, 20 to 1000 MHz
- low mainline loss, 2.1 dB typ.
- excellent coupling flatness, ±0.15 typ.
- aqueous washable
- protected by U.S. Patents 6,133,525 & 6,140,887

## Applications

- cable tv

ADC-6-10-75+  
ADC-6-10-75



CASE STYLE: CD542  
PRICE: \$6.95 ea. QTY (10)

### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

| Reel Size | Devices/Reel              |
|-----------|---------------------------|
| 7"        | 10, 20, 50, 100, 200, 500 |
| 13"       | 1000                      |



## Directional Coupler Electrical Specifications

| FREQ.<br>(MHz) | COUPLING<br>(dB) |          | MAINLINE LOSS <sup>1</sup><br>(dB) |                |                |                |                |                | DIRECTIVITY<br>(dB) |                |                | VSWR<br>(:1) | POWER<br>INPUT, W |            |
|----------------|------------------|----------|------------------------------------|----------------|----------------|----------------|----------------|----------------|---------------------|----------------|----------------|--------------|-------------------|------------|
|                | Nom.             | Flatness | L<br>Typ. Max.                     | M<br>Typ. Max. | U<br>Typ. Max. | L<br>Typ. Min. | M<br>Typ. Min. | U<br>Typ. Min. | L<br>Typ. Min.      | M<br>Typ. Min. | U<br>Typ. Min. |              | L<br>Max.         | MU<br>Max. |
| 20-1000        | 6.6±0.5          | ±0.5     | 2.1 2.8                            | 2.1 2.5        | 2.2 2.8        | 15 12          | 15 12          | 15 9           | 1.33                | 0.5            | 0.5            |              |                   |            |


L= 20-200 MHz M= 200-500 MHz U= 500-1000 MHz  
1. Mainline loss includes theoretical power loss at coupled port.

## Typical Performance Data

| Frequency<br>(MHz) | Mainline Loss<br>(dB)<br>In-Out | Coupling<br>(dB)<br>In-Cpl | Directivity<br>(dB) | Return Loss<br>(dB) |       |       |
|--------------------|---------------------------------|----------------------------|---------------------|---------------------|-------|-------|
|                    |                                 |                            |                     | In                  | Out   | Cpl   |
| 18.00              | 2.12                            | 6.65                       | 15.82               | 15.10               | 36.74 | 15.09 |
| 50.00              | 2.14                            | 6.66                       | 15.80               | 15.28               | 49.03 | 15.44 |
| 100.00             | 2.14                            | 6.70                       | 15.73               | 15.50               | 38.41 | 15.43 |
| 300.00             | 2.09                            | 6.72                       | 15.71               | 17.25               | 27.75 | 16.06 |
| 500.00             | 2.11                            | 6.53                       | 15.84               | 20.57               | 24.15 | 19.74 |
| 600.00             | 2.16                            | 6.48                       | 15.88               | 22.66               | 23.38 | 17.89 |
| 700.00             | 2.23                            | 6.51                       | 15.88               | 24.28               | 23.33 | 18.52 |
| 800.00             | 2.27                            | 6.61                       | 15.59               | 24.45               | 23.80 | 22.73 |
| 900.00             | 2.25                            | 6.67                       | 14.91               | 24.18               | 24.25 | 21.44 |
| 1000.00            | 2.26                            | 6.70                       | 13.81               | 24.01               | 23.70 | 19.57 |



## Electrical Schematic



\* ELECTRICAL SCHEMATIC IS FOR DIRECTIONAL COUPLER WITH INTERNAL TRANSFORMER(S) AND EXTERNAL TERMINATION.

### Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. D  
M119986  
ED-7094/1  
ADC-6-10-75  
WZ/TD/CP/AM  
120718