


Applications

- General purpose wireless
- Wireless infrastructure
- 3G, 4G, Multistandard
- Distributed Antenna Systems (DAS)



Product Features

- Usable bandwidth 65 MHz
- High attenuation
- Low EVM
- Balanced operation
- Ceramic Surface Mount Package (SMP-28C)
- Small Size: 7.00 x 5.50 x 1.24 mm
- Hermetic **RoHS** compliant, **Pb**-free

General Description


The 857071 is a high-performance IF SAW filter with a center frequency of 192.5MHz and 1.5 dB bandwidth of 65 MHz

It features excellent attenuation and pass band ripple, leading to outstanding EVM performance. 857071 is designed to be used in a balanced configuration, thereby eliminating the need for Baluns on the input and output. The high performance coupled with the small size of this surface mount filter makes it a natural choice for our customers filtering needs in demanding high data rate communications standards.

This device is RoHS compliant and Pb-free.

Functional Block Diagram

Top view



Pin Configuration

Pin #	Bal/Bal	Description
10		Input +
9		Input -
5		Output +
4		Output -
1,2,3		Case Ground
6,7,8		Case Ground

Ordering Information

Part No.	Description
857071	packaged part
857071-EVB	evaluation board

Standard T/R size = 3000 units/reel.

Specifications

Electrical Specifications ^(1, 2)

Specified Temperature Range: ⁽³⁾ +10 to +75 °C

Parameter ⁽⁴⁾	Conditions	Min	Typical ⁽⁵⁾	Max	Units
Center Frequency	f_o	-	192.5	-	MHz
Insertion Loss	at 192.5 MHz	-	17	19	dB
1.5 dB Bandwidth ⁽⁸⁾		65	67.5	-	MHz
35 dB Bandwidth ⁽⁸⁾		-	74	76	MHz
Passband Ripple ⁽⁶⁾	over f_o +/- 32.5 MHz	-	0.5	1.5	dB p-p
Absolute Delay	over f_o +/- 32.5 MHz	-	0.61	0.67	μs
Group Delay Ripple ⁽⁶⁾	over f_o +/- 32.5 MHz	-	60	100	ns p-p
Group Delay Ripple ⁽⁶⁾	Any 3.84 MHz channel over f_o +/- 32.5 MHz	-	55	70	ns p-p
EVM ⁽⁷⁾	Any 3.84 MHz channel over f_o +/- 32.5 MHz	-	2.6	3	%
Temperature Coefficient		-	-94	-	ppm / °C
Input Return Loss	over f_o +/- 32.5 MHz	7	8.7	-	dB
Output Return Loss	over f_o +/- 32.5 MHz	7	7.9	-	dB
Stopband Attenuation ⁽⁸⁾	5 – 100 MHz 100 – 152.5 MHz 230.5 – 231.0 MHz 231.0 – 237.0 MHz 237.0 – 310.0 MHz 310 – 500 MHz 500 – 860 MHz	50 35 32 35 35 35 50	60 38 36 37 40 56 60	- - - - - - -	dB
Source Impedance (balanced) ⁽⁹⁾		-	100	-	Ω
Load Impedance (balanced) ⁽⁹⁾		-	100	-	Ω

Notes:

1. All specifications are based on the TriQuint schematic for the main reference design shown on page 3
2. An external impedance matching network with ±2% tolerance will be necessary to achieve the proposed specifications
3. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
4. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
5. Typical values are based on average measurements at room temperature
6. This ripple defined as the worst peak to adjacent valley within the specified frequency ranges
7. The EVM specification is guaranteed by design and measured approximately in production
8. All bandwidths and attenuation measurements are referenced from minimum loss
9. This is the optimum impedance in order to achieve the performance shown

Absolute Maximum Ratings

Parameter	Rating
Operable Temperature	-40 to +85 °C
Storage Temperature	-40 to +85 °C
Input Power	10dBm (Measured with continuous sine wave signal. Expected Lifetime of greater than or equal to 10K Hrs at 55 °C)


Operation of this device outside the parameter ranges given above may cause permanent damage.

857071**192.5 MHz SAW Filter**


TriQuint 
SEMICONDUCTOR

Reference Design – 100Ω Bal Input, 100Ω Bal Output


Schematic



Notes:

1. Actual matching values may vary due to PCB layout and parasitic


PC Board



Notes:

Top, middle & bottom layers: 1 oz copper
 Substrates: FR4 dielectric, .031" thick
 Finish plating: Nickel: 3-8µm thick, Gold: .03-.2µm thick
 Hole plating: Copper min .0008µm thick

Mounting Configuration









Notes:

1. All dimensions are in millimeters.
2. This footprint represents a recommendation only.

Bill of Material


Reference Desg.	Value	Description	Manufacturer	Part Number
L1	56nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18AN56NJ00
L2	75nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18AN75NJ00
L3	75nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18AN75NJ00
L4	200nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18ANR20J00
L5	9.1nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18AN9N1D00
L6	9.1nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18AN9N1D00
L7	62nH	Coil Wire-wound, 0603, 5%	MuRata	LQW18AN62NJ00
C1	15pF	Chip Ceramic, 0603, 5%	MuRata	GRM1885C1H150JA01
R1	680Ω	Chip Ceramic, 1206, 5%	KOA	RM73B2BJ681
SMA	N/A	SMA connector	Johnson Components	142-0701-801
PCB	N/A	3-layer	multiple	960686

Typical Performance (at room temperature)



Mechanical Information

Package Information, Dimensions and Marking



Package Style: SMP-28C
Dimensions: 7.00 x 5.50 x 1.24 mm



Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m, over a 2-6 μ m Ni plating

All dimensions shown are nominal in millimeters
All tolerances are ± 0.15 mm except overall length and width
 ± 0.10 mm

The date code consists of: day of the current year (Julian, 3 digits), Y = last digit of the year (1 digit), and HH = hour (2 digits)

Tape and Reel Information

Standard T/R size = 3000 units/reel. All dimensions are in millimeters



Product Compliance Information

ESD Information



Caution! ESD-Sensitive Device

ESD Rating: 1A

Value: Passes ≥ 250 V min.

Test: Human Body Model (HBM)

Standard: JEDEC Standard JESD22-A114

ESD Rating: B

Value: Passes ≥ 200 V min.

Test: Machine Model (MM)

Standard: JEDEC Standard JESD22-A115

MSL Rating

Devices are Hermetic, therefore MSL is not applicable

Solderability

Compatible with the latest version of J-STD-020, lead free solder, 260°C

Refer to [Soldering Profile](#) for recommended guidelines.

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A ($C_{15}H_{12}Br_4O_2$) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: www.triquint.com
Email: info-sales@tqs.com

Tel: +1.407.886.8860
Fax: +1.407.886.7061

For technical questions and application information:

Email: flapplication.engineering@tqs.com

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.