


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 0.470–0.568 GHz
 Isolation: 20dB Min.
 Insertion loss: 0.35dB Max.
 VSWR: 1.22:1 Max.
 Operating Temperature: 0°C to +50°C
 Power: 100W Avg, 500W Peak

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: COAXIAL CIRCULATOR			
		PART NO.: CS-107			
DRAWN: Paiboon Luekhamhan	DATE: 05-24-2010	PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5	SIZE: N/A
APPROVED: T. Nguyen	DATE: 05-24-2010			REV: N/A	DWG. NO.: 84853
		THIRD ANGLE PROJECTION 		DO NOT SCALE THE DRAWING	