


Anaren

RF Power

**RoHS
Compliant**

Model D30A20Y4

**Surface Mount Attenuator
30 Watts**



General Specifications

| | |
|--------------------------|-----------------------|
| Resistive Element | Thick film |
| Substrate | Alumina |
| Terminals: | Matte Tin over Nickel |

Electrical Specifications

| | |
|---------------------------|--------------------|
| Attenuation Range: | 20 dB \pm .75 dB |
| Frequency Range; | DC – 2.0 GHz |
| Power: | 30 Watts |
| VSWR | 1.20:1 to 2 GHz |

Note: Tolerance is ± 0.010 ", unless otherwise specified. Designed to meet or exceed applicable portions of MIL-E-5400. Operating temperature is -55°C to 150°C (see chart for derating temperatures).


All dimensions in inches.

Specifications subject to change without notice.

Features:


- DC –2.0 GHz
- 30 Watts
- Alumina Ceramic
- Non-Nichrome Resistive Element
- Low VSWR
- 100% Tested
- RoHS Compliant

Outline Drawing



D30A20Y4 (097) Rev A

Anaren
What'll we think of next?™



Available on Tape
and Reel For Pick and
Place Manufacturing.

USA/Canada: (315) 432-8909
Toll Free: (800) 544-2414
Europe: +44 2392-232392





Typical Performance:

| RESISTOR VALUE CHART | | | | | |
|----------------------|-------------|-------------|-------------|-----------|---------------------|
| ATTENUATION | VALUE (A-B) | VALUE (A-C) | VALUE (B-C) | TOLERANCE | R.F.P. STOCKING P/N |
| 20dB±.75dB | 258Ω | 61Ω | 61Ω | ±4% | D30A20Y4 |

Power De-rating:

Mounting Footprint and Procedure:



SUGGESTED MOUNTING PROCEDURES:


1. MAKE SURE THAT THE DEVICES ARE MOUNTED ON FLAT SURFACES (.001" UNDER THE DEVICE) TO OPTIMIZE THE HEAT TRANSFER.
2. DRILL & TAP THE HEATSINK FOR THE APPROPRIATE THREAD SIZE TO BE USED.
3. COAT HEATSINK WITH A MINIMUM AMOUNT OF HIGH QUALITY SILICONE GREASE (.001" MAX. THICKNESS).
4. POSITION DEVICE ON MOUNTING SURFACE & SECURE USING SOCKET HEAD SCREWS, FLAT & SPLIT WASHER. TORQUE SCREWS TO THE APPROPRIATE VALUE. MAKE SURE THAT THE DEVICE IS FLAT AGAINST THE HEATSINK. (CARE SHOULD BE TAKEN TO AVOID UPWARD PRESSURE OF THE LEADS TOWARDS THE LID).
5. SOLDER LEADS IN PLACE USING APPROPRIATE SOLDER WITH A CONTROLLED TEMPERATURE IRON.

** FOR MORE DETAILS CONTACT FACTORY **

D30A20Y4 (097) Rev A

USA/Canada: (315) 432-8909
Toll Free: (800) 544-2414
Europe: +44 2392-232392

Available on Tape and
Reel For Pick and Place
Manufacturing.



Anaren
What'll we think of next?™