

## **Specifications**

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	360		390
Insertion Loss (dB)		< .30	.40
Isolation (dB)	20	> 23	
Return Loss (dB)	20	> 23	

## Notes:

- 1. Typical Values Represent Mid-Band Performance @ +23 °C.
- 2. Iso-Attenuator Flange held to  $+85^{\circ}\text{C}$ ; 30 Min. maximum Duration.
- 3. Tab dims: 1.00[.039]Width x 3.0[.12]Length x .20[.008]Thick

## Power & Temperature Ratings

Parameter	Maximum		
Forward PWR Peak/AVG	1000/200 Watts		
Reverse Power CW	100 Watts		
Attenuator Rating (See Note 2)	100 Watts		
Attenuation (P3)	30dB±1dB		
Operating Temperature	-20 to +85° C		
Storage Temperature	-40 to +95° C		

## CW 100W-30dB ISO-ATTENUATOR MODEL: RFSL2130-A30

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS (INCHES): TOLERANCES ARE:	THIRD ANGLE PROJECTION		DECL (A)				
1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° 2 PLACE DECIMAL ±.10 [±.004] SURFACE ROUGHNESS 16/	APPROVALS	DATE					
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1	DRAWN BY: HV	04/19/13					
DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI 546.1	CHECKED BY: P.T	04/20/13	TITLE				
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE	DESIGN BY: P.T	12/12/12	H OUTLINE/OFTO				
CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES.	ENGINEER BY: P.T	01/15/13					
THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED. NOR SHALL IT BE	MFG. ENGR. L.T	04/21/13	SIZE	SIZE CAGE NO. DWG NO.		REV.	
DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."	Q.A.		A   0.1.0.2.1.0.1			0 420 00	1
	PROG. MGMT/MKT		A		3L213	0-A30-OS	ı
DO NOT SCALE DRAWING			SCALE	E: FULL		SHEET 1 C	F 1
	_				•	•	