



5300 Beethoven Street, Los Angeles, CA 90066
TEL: (310)306-5556 • FAX: (310)821-7413
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5302027

1.8 - 2.0 GHz
12 WATTS

Solid State Band-specific High Power RF Amplifier

The 5302027 is a 12 Watt band-specific amplifier that covers the 1.8 – 2.0 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5302027 comes with an extended

	Parameter	Specification @ 25° C
<u>Electrical</u>		
1	Frequency Range	1.8 – 2.0 GHz
2	Instantaneous Bandwidth	60 MHz min
3	Saturated Output Power	12 Watts typical
4	Power Output @ 1dB Comp.	10 Watts min
5	Power Output CDMA	2 Watts typical
6	Small Signal Gain	+45 dB min
7	Gain Flatness	± 1.0 dB max
8	IP ₃	+50 dBm typical
9	Input VSWR	2:1 max
10	Harmonics	-20 dBc typical @ 10 Watts
11	Spurious Signals	> -60 dBc typical @ 10 Watts
12	Input/Output Impedance	50 Ohms nominal
13	DC Input Current	3 Amps max
14	DC Input	13 VDC nominal
15	RF Input	-5 dBm max
16	RF Input Signal Format	CW/AM/FM/PM/Pulse
17	Class of Operation	A/AB
<u>Mechanical</u>		
18	Dimensions	6.0" x 2.75" x 0.83"
19	Weight	2 lb. max
20	Connectors	SMA female
21	Grounding	Chassis
22	Cooling	Adequate Heatsink Required
<u>Environmental</u>		
23	Operating Temperature	0° C to +50° C
24	Operating Humidity	95% Non-condensing
25	Operating Altitude	Up to 10,000' Above Sea Level
26	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



Approved By: _____ Date: _____