

## HyperLink Wireless 5.4 GHz 23 dBi High Performance Parabolic Dish Wireless LAN Antenna

Model: HG5423D

### Applications and Features

---

**Applications:**

- 5.4 GHz Band Applications
- Unlicensed European 5.4 GHz Band Applications
- IEEE 802.11a Wireless LAN
- WiFi Systems
- Radio Local Area Networks (RLAN)
- Fixed Wireless Access Systems (FWA)
- WiMAX Technology
- Long-range Directional Applications
- Wireless Bridges
- Backhaul Applications

**Features:**

- Superior performance
- Aluminum reflector dish
- UV Stable light gray polymer finish
- All weather operation
- Vertical or horizontal polarized mounting
- Includes tilt and swivel mast mount kit
- Optional radome cover kits available
- RoHS Compliant



### Description

---

#### Superior Performance

The HyperGain® 5.4GHz High-Performance Parabolic Dish WiFi Antenna is ideal for directional 5.4GHz 802.11a band applications as well as applications in the European unlicensed 5.4 GHz band. It features 23 dBi gain with a 9° beam-width. These antennas can be oriented for either vertical or horizontal polarization.

#### Rugged and Weatherproof

The reflector dish of these antennas are constructed from high quality aluminum which gives them superior strength. The dish is coated in a light gray UV-inhibited polymer for durability and aesthetics. The small diameter of the dish helps minimize wind loading.

These antennas are supplied with a tilt and swivel mast mount kit. This allows installation at various degrees of incline for easy alignment. The HG5423D can be adjusted from 0° to 60°.



**Radome Cover Kits**



HyperGain® Radome Covers are an ideal way to provide additional protection to our parabolic dish antennas. These light weight radome kits feature fiberglass construction and UV stable gray finish. Drain holes are provided on the radome cover to help prevent moisture build-up inside the dish antenna.

These radome kits bolt directly to the dish antennas with the provided stainless steel hardware. Drilling mounting holes in the antenna is not required. The radome cover can be attached to existing antennas already mounted in the field or pre-assemble to the antenna before mounting.

**Specifications**

<b>Frequency</b>	5470-5725 MHz
<b>Gain</b>	23 dBi
<b>Polarization</b>	Horizontal or Vertical
<b>Horizontal Beam Width</b>	9°
<b>Vertical Beam Width</b>	9°
<b>Front to Back Ratio</b>	30 dB
<b>Impedance</b>	50 Ohm
<b>Max. Input Power</b>	100 Watts
<b>VSWR</b>	< 1.5:1 avg.
<b>Weight</b>	6.6 lbs. (3 kg)
<b>Diameter</b>	17.2 in. (436.8 mm)
<b>Mounting</b>	2 in. (50.8 mm) diameter mast max.
<b>Operating Temperature</b>	-40° C to 85° C (-40° F to 185° F)
<b>Lighting Protection</b>	DC Short
<b>RoHS Compliant</b>	Yes
<b>Connector</b>	N-Female
<b>Radome Cover Part Number</b>	HGR-04

RF Antenna Patterns

