




This document contains proprietary information and such information may not be disclosed to others for any purposes, nor used for sales/marketing/procurement purposes without written permission

本文件包含专有信息，没有书面许可，该信息不能以任何形式披露给第三方，也不能用于任何目的的买卖、销售及采购。



产品型号 type	配接电缆 cable type
L29-J554	7/8"波纹(环形)铜管介质发泡电缆 LDF5-50A (HELIAX ANDREW)

Electrical Characteristics:

- Characteristic Impedance: $50\ \Omega$
- Frequency range: DC~3Ghz
- Contact resistance
Center conductor: $\leq 1.0\ m\Omega$
Out conductor: $\leq 0.5\ m\Omega$
- Insulation resistance: $\geq 10000M\Omega$
- Insulator withstanding: 4000V
- VSWR: ≤ 1.5
- Durability: 500cycles

Application: IEC 60169-4

Material&Finishing

- Center contact:
Male: brass, silver plated
- Out conductor: brass, silver plated
Other metal parts: brass, nickel plated
- Insulators: PTFE
- Gasket: silicone rubber

主要性能指标:

- 特性阻抗: $50\ \Omega$
- 频率范围: DC~3Ghz
- 接触电阻:
中心导体: $\leq 1.0\ m\Omega$
外导体: $\leq 0.5\ m\Omega$
- 绝缘电阻: $\geq 10000M\Omega$
- 介质耐压: 4000V
- 电压驻波比: ≤ 1.5
- 插拔次数: 500次

执行标准: IEC 60169-4

材料和镀层

- 中心接触件:
插针: 黄铜, 镀银
- 外导体: 黄铜, 镀银
其它金属零件: 黄铜, 镀镍
- 绝缘子: 聚四氟乙烯
- 密封圈: 硅橡胶

	SCALE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	1.5:1	
L29-J554 RF COAXIAL CONNECTOR		西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.
NAME	DATE	
DRAWN		
CHECKED		
APPROVED		