



Model: SW-V040-3S

Description:..... SP3T, Reflective, PIN-Switch

Operating Frequency:..... 0.1 – 18 GHz

Insertion Loss:

0.1 – 0.5 GHz	0.5 – 10 GHz	10 – 18 GHz
2.8 dB Max	2.5 dB Max	3.2 dB Max

Isolation:

0.1 – 10 GHz	10 – 18 GHz
65 dB Min	55 dB Min

VSWR ("ON" paths):..... 1.9:1 Max

Rise/Fall time (10% to 90% RF, 90% to 10% RF): ... 35 ns Max

On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF):..... 120 ns Max

Phase Error (Port-to-Port): $\pm 10^\circ$ max

Operating Power:..... CW&AVG..... +27dBm Max

..... Peak: 8W @ 1 μ S PW Max

Control Input Characteristics: TTL / Unit-Load / Floating-High

Control Logic:..... 3-Controls, Logic "0" = RF Path "ON"

Power Supplies:..... +5(± 0.25)V @ 60mA Max

..... -12(± 0.5)V @ 60mA Max

Connectors (RF): SMA (f), Removable

Connectors (Supplies/Controls) Solder Pins

Impedance: 50 Ohms Nominal

Quality:..... Best-Commercial-Grade

Environmental Ratings:

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}

Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)

Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)

Vibration: MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)

Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)

Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

A2 [+5(± 0.25)V / -15(± 0.5)V]

A3 [+12(± 0.5)V / -12(± 0.5)V]

A4 [+15(± 0.5)V / -15(± 0.5)V]

■ **RF Connectors**

B1 [J1 – J3 Ports with SMA(M)]

B2 [All SMA (M)]

B3 [COM Port with SMA(M)]


■ **Control Function**

F1 [Inverse Logic, ("1" = Path "ON")]



Model: SW-V040-3S

Outline



Weight	Tolerances
1.0 oz [28.4g]	±0.015" [±0.38mm]