


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 0.7–4.3 GHz
 Insertion Loss: 0.75dB Max.
 Isolation: 20dB Min.
 VSWR: 1.40:1 Max.
 Phase Balance: ± 6 Deg. Max.
 Amplitude Balance: ± 0.3 dB Max.
 Power: 20W (Load vswr@1.2)

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE:		SHEET: N/A	
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		PART NO.		2WAY-POWER DIVIDER	
DRAWN: Paiboon Luekhamhan		DATE: 06-27-2007		CAGE CODE: OD2L5		PS2-59/NF	
APPROVED: T. Nguyen		DATE: 06-27-2007		SIZE: N/A		REV: N/A	
				DO NOT SCALE THE DRAWING		DWG. NO. 82845	