




This document contains proprietary information and such information may not be disclosed to others for any purposes, nor used for sales/marketing/procurement purposes without written permission

本文件包含专有信息，没有书面许可，该信息不能以任何形式披露给第三方，也不能用于任何目的的买卖、销售及采购。



Electrical Characteristics:

1. Characteristic Impedance: $50\ \Omega$
2. Frequency range: DC~2.0GHz
3. Contact resistance
Center conductor: $\leq 5.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
4. Insulation resistance: $\geq 500M\Omega$
5. Insulator withstanding: 500V
6. Durability: 500cycles

Application: Q/FD20131-2006

Material&Finishing

1. Center contact:
Male: brass, gold plated
2. Body: brass, gold plated
3. Insulators: PTFE

主要性能指标:

1. 特性阻抗: $50\ \Omega$
2. 频率范围: DC~2.0GHz
3. 接触电阻:
中心导体: $\leq 5.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
4. 绝缘电阻: $\geq 500M\Omega$
5. 介质耐压: 500V
6. 插拔次数: 500次

执行标准: Q/FD20131-2006

材料和镀层

1. 中心接触件:
插针: 黄铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

		SCALE	DSD-JJ-1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
		2.5:1		
NAME		DATE	RF COAXIAL ADAPTER	西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.
DRAWN				
CHECKED				
APPROVED				