



MMCX Jack to MMCX Jack Adapter

TECHNICAL DATA SHEET

PE9523

MMCX Jack to MMCX Jack Adapter

Configuration

Connector 1MMCX JackImpedance 150 OhmsConnector 2MMCX JackImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Size

Length, in [mm] 0.473 [12.01] Width/Dia., in [mm] 0.158 [4.01]

Connector 1

Type MMCX Jack
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Connector 2

Type MMCX Jack
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

MMCX Jack to MMCX Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MMCX Jack to MMCX Jack Adapter PE9523

URL: http://www.pasternack.com/mmcx-jack-mmcx-jack-straight-adapter-pe9523-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9523 CAD Drawing

MMCX Jack to MMCX Jack Adapter

