




Voltage Control Phase Shifter 2-4GHz



Features

- Wide Band Operation 2-4GHz
- 360° Phase Shift
- Low Insertion Loss and Low Phase Error
- Single Control Operation
- Customization available upon request

Electrical Specifications, TA = +25 °C

Description	PN:RVPT0204GBC			
	Voltage Control Phase Shifter			
Parameters	Min	Typ.	Max	Units
Frequency Range	2 ~ 4			GHz
Phase Range		360		°
Insertion Loss			5.5	dB
Insertion Loss Temperature Coefficient		0.1		dB/°C
Phase Flatness			±15	°
Control Voltage	0	12		V
Input VSWR		2.2	2.5	ratio
Output VSWR		2.2	2.5	ratio
Input Power for 1 dB Compression		25		dBm
IM3		35		dBc
Weight	1.2			ounces
Impedance	50			Ω
current	5			mA
Input /Output Connector	SMA-Female (Standard)			
Finishing	Gold Plating			
Material	Aluminum			
Seal	Hermetically Sealed (optional)			



RF-LAMBDA

LEADER OF BROADBAND SOLUTIONS

RVPT0204GBC

Absolute Maximum Ratings

Control Voltage	0~ 13V
RF Input power	+27dBm
Operating Temperature(°C)	-45 ~ +85
Storage Temperature(°C)	-50 ~ +125

Ordering Information


Part No	ECCN	Description
RVPT0204GBC	EAR99	2-4GHz Voltage Control Phase Shifter

Environment specifications


Operational Temperature (°C)	-45 ~ +85
Storage Temperature (°C)	-50 ~ +125
Altitude	30,000 ft. (Epoxy Seal Controlled environment) 60,000 ft 1.0psi min (Hermetically Seal Un-controlled environment) (Optional)
Vibration	25g rms (15 degree 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msc half sin wave, 3 axis both directions

Typical performance plots


Insertion Loss vs. Frequency




Input Return Loss vs. Frequency



Output Return Loss vs. Frequency



Phase Shift vs. Frequency



Voltage Control Phase Shifter 2-4GHz




RF-LAMBDA

LEADER OF BROADBAND SOLUTIONS


RVPT0204GBC

Phase Shift vs. Voltage



Outline Drawing:

All Dimensions in mm (inches)



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.