
A I B I C I D I E I F I G I H I J I K I L I M I N I P I O

Coaxial Adapter 2.4 mm Female to 2.4 mm Female



S2	22 SW	R 10	0 m / R	EF 1	1	1: 1.0905	38	. 451 9	37 500	GHz
L										
									Max	
ŀ									+	
ı										
L										
H									_	
-										
H									+	
										<u>1</u>
									1	o Yang
					 			L	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	٦
Ł								- Annual Contraction of the Cont	ฟ์	
	START	. 050 0	00 000 G	Hz		5	TOP 40.0	000 000	000 G	Hz

2.0	Environment specifications				
2.1	Opt. Temp.	-55°C~+165°C			
2.2	Storage Temp.	-60°C~+185°C			
2.3	Altitude	45000 ft			
2.4	Vibration	10g rms (15 degree 2KHz)			
2.5	Humidity	100% RH at 35c, 95%RH at 40 °c			
2.6	Shock	20G for 11msc			

1.0	Mechanical Specifications				
1.1	2.4mm	STD 287-2007			
1.2	2.4mm	STD 287-2007			
1.3	MIL	MIL-G-45204			

PN	Frequency (GHz)	Impedance (Ω)	VSWR (max)	Insulate material	Material	Center PIN	
RFCARAWFWF	DC-50	50	1.20	PEI	Stainless Steel SU303	Brass with Gold plating	

PAGE 1 OF	1		DATE JAN	18 th 2003	1	
	PROPRIETARY INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RE-AMBIDA EXCEPTAS SPECIFICALLY AUTHORIZED IN WEUTURGS IT RE-AMBIDA. THE HOLDER OF THIS DOUCUMENT SHALL KEEP ALL INFORMATION CONTAINED HERBILLOONIDENTIAL AND SHALL PROTECT SAME IN THE					
PROPERTY OF RF-LAMBDA EXCEPT AS AUTHORIZED IN WRUTUBG BT RF-LAMB						
HEREIN CONFIDENTIAL AND SHALL PRO						
OF ALL THIRD PARTIES AND SHALL US	WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY					
		CAD MODE	L REVISION	1		
	COAXIAL ADAPTER RFCARAWFWF					
KFGAKAV						
	RFLVR54					
	DRAWING NUMBER		١,			
www.rflambda.com	www.rflambda.com					
RF-LAMBDA	SIZE	SHEETS	0.5			
KF-LAMBUA	LT	1	OF	1	l	