

Plug-In

Power Splitter/Combiner

2 Way-0° 50Ω 5 to 2000 MHz

MSC-2-11+
MSC-2-11



Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.125W max.
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

SUM PORT	1
PORT 1	5
PORT 2	6
GROUND	2,3,4,7,8
CASE GROUND	2,3,4,7,8

Features

- very wideband, 5 to 2000 MHz
- low insertion loss, 0.6 dB typ.
- rugged welded case

Applications

- cellular
- GPS
- instrumentation
- defense communications

CASE STYLE: A03
PRICE: \$34.20 ea. QTY. (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications




FREQ. RANGE (MHz)	ISOLATION (dB)						INSERTION LOSS (dB) ABOVE 3.0 dB						PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)		
	L		M		U		L		M		U		L		M		U	
	Typ.	Min	Typ.	Min	Typ.	Min	Typ.	Max.	Typ.	Max.	Typ.	Max.	Max.	Max.	Max.	Max.	Max.	Max.
f _L -f _U																		
5-2000	18	16	20	16	18	11	0.6	0.8	0.6	0.8	1.2	1.8	2.0	3.0	5.0	0.2	0.3	0.5

L = low range [f_L to 10 f_L] M = mid range [10 f_L to f_U/2] U = upper range [f_U/2 to f_U]

Typical Performance Data

Frequency (MHz)	Total Loss ¹ (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
5.00	3.55	3.56	0.01	18.23	0.03	1.80	1.64	1.58
50.00	3.55	3.57	0.02	18.58	0.02	1.79	1.65	1.59
75.00	3.58	3.58	0.00	18.62	0.09	1.78	1.65	1.59
125.00	3.58	3.60	0.02	18.72	0.03	1.77	1.66	1.59
175.00	3.58	3.59	0.01	18.82	0.00	1.76	1.66	1.60
275.00	3.58	3.60	0.01	19.08	0.02	1.74	1.67	1.61
450.00	3.60	3.59	0.00	19.80	0.13	1.70	1.67	1.61
550.00	3.61	3.60	0.01	20.38	0.02	1.67	1.67	1.62
700.00	3.61	3.59	0.02	21.58	0.04	1.62	1.66	1.62
1000.00	3.69	3.66	0.03	26.52	0.13	1.51	1.63	1.61
1200.00	3.59	3.53	0.05	34.48	0.14	1.41	1.60	1.60
1400.00	3.66	3.58	0.07	30.65	0.25	1.30	1.55	1.57
1600.00	3.63	3.55	0.08	22.54	0.26	1.18	1.49	1.53
1800.00	3.64	3.54	0.11	17.78	0.45	1.08	1.41	1.45
2000.00	3.80	3.68	0.12	14.47	0.44	1.20	1.33	1.36


1. Total Loss = Insertion Loss + 3dB splitter loss.



electrical schematic



Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.480	.500	.390	.405	.210	.230
12.19	12.70	9.91	10.29	5.33	5.84

G	H	J	K	wt
.100	.20	.14	.020	grams
2.54	5.08	3.56	0.51	2.3

Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine **Mini-Circuits** Provides ACTUAL Data Instantly at minicircuits.com
IFIRF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. B
M127604
MSC-2-11
HY/TD/CP/AM
100602