



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## Approval Sheet For Product Specification

Issued Date: February, 16, 2007

Product Name: SAW Filter 1885 MHz SMD 3.0X3.0 mm

TST Parts No.:TA0629A

Customer Parts No.:\_\_\_\_\_

Company:\_\_\_\_\_

Division:\_\_\_\_\_

Approved by : \_\_\_\_\_

Date:\_\_\_\_\_

Checked by:\_\_\_\_\_ Paul Ni

Approval by:\_\_\_\_\_ Francis Chen

Date:\_\_\_\_\_ 02, 16, 2007



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## SAW Filter 1885 MHz

MODEL NO.: TA0629A

REV. NO : 1.0

### A. MAXIMUM RATING:


1. Input Power Level: 10 dB<sub>m</sub>
2. DC voltage: 3 V
3. Operating Temperature: -30°C to +85°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant  
Lead free  
Lead-free soldering


### B. ELECTRICAL CHARACTERISTICS:

| Item                                               | Min. | Typ. | Max. |
|----------------------------------------------------|------|------|------|
| Center frequency Fc (dB)                           | -    | 1885 | -    |
| Insertion loss within 1850 ~1920 MHz IL (dB)       | -    | 2.4  | 3.8  |
| Amplitude ripple (p-p) within 1850 ~ 1920 MHz (dB) | -    | 1.2  | 2.5  |
| <b>Attenuation</b> (Reference level from 0 dB)     |      |      |      |
| D.C. ~ 1542.5 MHz (dB)                             | 14.0 | 24.5 | -    |
| 1542.5 ~ 1752.5 MHz (dB)                           | 15.0 | 26.0 | -    |
| 1752.5 ~ 1827.5 MHz (dB)                           | 10.0 | 17.5 | -    |
| 1962.5 ~ 3162.5 MHz (dB)                           | 17.0 | 30.0 | -    |
| 3162.5 ~ 4000 MHz (dB)                             | 14.0 | 30.0 | -    |
| VSWR within 1850 ~1920 MHz                         | -    | 1.9  | 2.6  |
| Source impedance Z <sub>s</sub> (Ω)                | -    | 50   | -    |
| Load impedance Z <sub>L</sub> (Ω)                  | -    | 50   | -    |

### C. MEASUREMENT CIRCUIT:




## D.OUTLINE DRAWING:



$\triangle$  : Year Code(2007→7,···2009→9)



$\square$  : Date Code(Follow the table from planner each year)

## E. PCB Footprint :




## F. Frequency Characteristics :

### Transfer function




## Reflections Functions :

### S11 VSWR




### S22 VSWR




## G. PACKING:

### 1. REEL DIMENSION



### 2. TAPE DIMENSION



## H. RECOMMENDED REFLOW PROFILE:

