

DESCRIPTION:

PMI MODEL NUMBER PDVAN-2040-60-8 IS AN 8 BIT PROGRAMMABLE 60 DB PIN DIODE ATTENUATOR WITH STEP RESOLUTION AS LOW AS 0.25 DB OVER THE FREQUENCY RANGE OF 2.0 GHZ TO 4.0 GHZ.

SPECIFICATIONS:

- FREQUENCY: 2.0 GHz TO 4.0 GHz
- MEAN ATTENUATION RANGE 60dB
- INSERTION LOSS 2.0 dB MAX
- VSWR: 2.0:1 MAX
- POWER RATING: +20dBm (Operating)
+30dBm (Survival)
- ATTENUATION FLATNESS:
 - @ 10 dB ±0.45 dB
 - @ 20dB ±0.8 dB
 - @ 40dB ±1.5 dB
 - @ 60dB ±1.6 dB



- | | |
|----------------------|---|
| ● SWITCHING TIME | 500 nsec MAX |
| ● DIGITAL CONTROL | 8 BIT Positive True, Binary TTL |
| ● MONOTONICITY: | GUARANTEED |
| ● POWER SUPPLY | +12V to +15V @ 150mA MAX
-12V to -15V @ 75mA MAX |
| ● PWR/CTL CONNECTORS | 15 PIN Micro-D-Female (MATING CONNECTOR SUPPLIED) |
| ● RF CONNECTORS | SMA - Female |
| ● FINISH | PAINTED GRAY |
| ● SIZE | (L) 2.00" X (W) 1.80" X(H) 0.50" |

ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	ORIGINAL RELEASE	11/3/11	



CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-ff.com
E-MAIL: sales@pmi-ff.com
ISO 9001:2008 CERTIFIED



TITLE		PRODUCT FEATURE			
APPROVALS	DATE	PDVAN-2040-60-8			
DRAWN					
<i>RM</i>	11/3/11				
CHECKED					
ISSUED		SIZE	FSCM NO.	DWG NO.	REV.
		A	05XQ0	270XXXX	-
SCALE		N:S	SHEET		1 OF 1