

## Full Spectrum GNSS Antenna



- High-end Geodetic Antenna
- Topcon's TA-5 vertical convex dipole antenna element for full spectrum GNSS signal tracking
- Topcon newly design semi-hemispherical convex impedance groundplane
- Environmentally robust and sealed
- Minimized phase center offset variations in vertical within GNSS frequency band. Significant increase of low elevated satellites tracking.



### Unmatched Signal Tracking and Multipath Reduction

Topcon's newly designed PN-A5 antenna combines the Topcon's new TA-5 full spectrum GNSS antenna element with an innovative convex impedance ground plane. The TA-5 antenna element utilizes an array of vertical dipoles to provide highly sensitive and stable Full Wave signal tracking for all existing and planned GNSS signals. Topcon's new convex impedance ground plane provides improved multipath mitigation while providing minimum signal loss for satellites tracked to the horizon.

### Topcon TotalCare

TotalCare provides a complete support and training solution for all of your positioning products, with online resources and real live people who are ready to help, and care about your productivity. Get expert training from Topcon University's large collection of online training materials, including quick-guides and videos.

Receive expert help directly from Topcon's Technical Support group. Access software and firmware updates, the latest Topcon publications, and exclusive access to the experts at Topcon... all right from your computer or your mobile device.

Please visit the TotalCare website to learn more.  
[topcontotalcare.com](http://topcontotalcare.com)



7400 National Drive • Livermore • CA 94550  
 (925) 245-8300

Specifications subject to change without notice. ©2012 Topcon Corporation  
 All rights reserved. P/N: 7010-2088 Rev. B Printed in U.S.A. 4/12

The *Bluetooth*® word mark and logos are registered trademarks owned by *Bluetooth SIG, Inc.* and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

### SPECIFICATIONS

#### Dimensions

Antenna without Anti-snow Dome	380 mm (D) x 262 mm (H)
With Topcon Anti-snow Spherical Dome	380 mm (D) x 292 mm (H)
With SCIGN Anti-snow Short Dome	415 mm (D) x 287 mm (H)

#### Weight

Antenna	6.7 kg
Topcon Anti-snow Spherical Dome	1.1 kg
Antenna w/ Topcon Anti-snow Spherical Dome	7.8 kg

#### Power

Input Voltage:	+3 to +12 VDC
Current Consumption:	100 mA (typical)
Connector:	N-type

#### Environmental

MIL-STD-810G	
Temperature	(Methods 501.5, 502.5)
Operating Range:	-50°C to +70°C
Storage Range:	-55°C to +85°C
Humidity	95%, Method 507.5
Vibration	Method 514.6, Broad band noise (random vibration), along each of 3 axes, Category 4, table 514.6C-IV
Mechanical Shock	Method 516.6, along each of 3 axes. Procedure I - Functional Shock, Table 516.6-I, Fig. 516.6-8, accelerative forces up to 40g.
IP Rating	IEC 60529 IP67
Drop Test	Repeated drops from the height of 1 m on concrete surface. All sides - top, bottom and border. (with Topcon or SCIGN Dome).
RoHS Compliant	Yes

#### Performance

Operating Frequency Range	
Lower band	1230 MHz ± 70 MHz (L5, E5B, E3, L2, G2, E4, E6)
Upper band	1565 MHz ± 50 MHz (E2, L1, E1, G1, OmniStar, SBAS, CDGPS)
Out-of-Band Rejection	
Upper band (1568.5 MHz ± 100 MHz)	-30 dBc (typical)
Upper band (1568.5 MHz ± 150 MHz)	-50 dBc (typical)
Lower band (1232 MHz ± 100 MHz)	-30 dBc (typical)
Lower band (1232 MHz ± 150 MHz)	-50 dBc (typical)
Other bands	
f < 1000 MHz	-80 dBc (typical)
f > 1750 MHz	-80 dBc (typical)
LNA Gain	
Gain at Zenith (90°)	43 dB (typical)
Gain Roll-Off (from Zenith to Horizon)	Lower band: +6 dB (typical)    Upper band: +4.7 dB (typical)
Noise Figure	Lower band: -12 dB (typical)    Upper band: -10 dB (typical)
VSWR	1.0 dB (typical)
Differential Propagation Delay (typical)	1.5 : 1
Nominal Impedance	Lower band: 3 ns (maximum)    Upper band: 3 ns (maximum) 50 Ohm

Your local Authorized Topcon dealer is: