

# 2.4mm Male Connector Clamp/Solder Attachment For PE-SR405AL, PE-SR405FL, RG405



## TECHNICAL DATA SHEET

PE44345

Configuration

Connector 2.4mm Male

Connector Interface Type PE-SR405AL,PE-SR405FL,RG405

Attachment Method (Shield/Contact)

Clamp/Solder

Straight

Body Style Straight

**Electrical Specifications** 

Frequency Range, GHz DC to 50 Impedance, Ohms 50

Maximum VSWR 1.3:1

**Mechanical Specifications** 

Size

 Length, in [mm]
 0.95 [24.13]

 Width/Dia., in [mm]
 0.312 [7.92]

Weight, lbs [g] 0.013 [5.9]

Connector

Type 2.4mm Male

Contact Material and Plating Beryllium Copper, Gold

Contact Plating Specification MIL-G-45204

Coupling Nut Material and Plating Passivated Stainless Steel

Coupling Nut Plating Specification ASTM A380 Hex Size, in. 5/16
Torque, in-lbs [Nm] 8 [0.9]

Body Material and Plating Passivated Stainless Steel

Body Plating Specification ASTM A380 Dielectric Type Noryl

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes
REACH Compliant 06/18/2012

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Male Connector Clamp/Solder Attachment For PE-SR405AL, PE-SR405FL, RG405 PE44345

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.





## 2.4mm Male Connector Clamp/Solder Attachment For PE-SR405AL, PE-SR405FL, RG405



### **TECHNICAL DATA SHEET**

**PE44345** 

#### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level


2.4mm Male Connector Clamp/Solder Attachment For PE-SR405AL, PE-SR405FL, RG405 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Male Connector Clamp/Solder Attachment For PE-SR405AL, PE-SR405FL, RG405 PE44345

URL: http://www.pasternack.com/2.4mm-male-standard-pe-sr405al-pe-sr405fl-rg405-connector-pe44345-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.







Pasternack Enterprises, Inc. P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

8

SHARP

â

 $\ddot{\circ}$ 

INSERT CABLE THRU ADAPTER UNTIL IT

CONDUCTOR TO ADAPTER & TRIM BOTTOMS OUT. SOLDER OUTER

DIELECTRIC AS SHOWN IN (B)

Б,

SLIDE CLAMP NUT OVER CABLE. STRIP CABLE AS SHOWN IN (A). DO NOT NICK

DIELECTRIC.

ASSEMBLY PROCEDURES