


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 2.5–2.7 GHz
 Insertion Loss: 0.9dB Max.
 Isolation: 17dB Min.
 VSWR: 1.55:1 Max.
 Phase Balance: ± 7 Deg. Max.
 Amplitude Balance: 0.4dB Max.
 Power: 20W (Load vswr@1.2)

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 3-WAY POWER DIVIDER		SHEET:
DRAWN: Paiboon Luekhamhan		DATE: 02-23-1998		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)
APPROVED: T. Nguyen		DATE: 02-23-1998		THIRD ANGLE PROJECTION
CAGE CODE: OD2L5		SIZE: A		REV: N/A
DO NOT SCALE THE DRAWING		DWG NO. 80917		