TITLE:

GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS

E	PER ECN 0942	Andy 961223	TITLE : GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS
D	PER ECN 0845	Andy 960716	
С	PER ECN 0778	2011son 960312	Product Specification
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
			· · · · · · · · · · · · · · · · · · ·

DOCUMENT NO

PS - 73598-0104

Prepared By: R. Fields

Date:941114 SHEET NO.

Approved By:

1 of 10

SMB75-PS

1.0 SCOPE

This specification covers the performance requirements and characteristics for SPECIAL 75 OHM SMB SERIES CONNECTORS, using 50 OHM's mechanical characteristics.

2.0 APPLICABLE DOCUMENTS SPECIFICATIONS

2.1 Per applicable Molex Material Spec. refer to Sales and Engineering Drawings.

3.0 PRODUCT DESCRIPTION

3.1 Product Name

SPECIAL 75 OHM SMB SERIES CONNECTORS.

3.2 Material

Refer to respective sales drawing

3.3 Finishes

Refer to respective sales drawing.

4.0 RATINGS

Item	Rating
Working Voltage	500 VRMS @ Sea Level
Impedance	75 Ohm Nominal
Frequency Range	dc to 4 GHz
Temperature Range	-65 deg. C to +165 deg. C

5.0 PERFORMANCE SPECIFICATIONS

4				
E	PER ECN 0942	Andy 961223	TITLE : GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS	
D	PER ECN 0845	Andy 960716		
С	PER ECN 0778	20des 960312	Product Specification	
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
DOCUM	PS - 735	598-0104	Prepared By: R. Fulls Checked By: Date: 941114 Approved By: Date: 961227 Approved By: Date: 961230	

5.1 Electrical Performance

Test Item	Test Spec.	Test Condition
Insertion Loss	Initial: 0.20 x (f) ^{1/2} After environment: N/A f(GHz): test frequency	dc to 4 GHz
Insulation Resistance	1000 megohms min.	500 V DC.
Dielectric Withstanding Voltage	1000 volts rms. min.	at sea level
VSWR	Initial:1.10: 1 per mated pair After environment: N/A f (GHz): test frequency	dc to 1 GHz
Contact Resistance	Center Contact: 6.0 milliohms Max. Outer Contact: Initial:3.0 milliohms Max. After environment: N/A	

E	PER ECN 0942	Andy 961223	TITLE : GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS	
D	PER ECN 0845	Andy 960716		
С	PER ECN 0778	Water 960312	Product Specification	
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
DOCUM	PS - 735	598-0104	Prepared Ry: P Zulla Date: 041114 SHEET NO.	

5.2 Mechanical Performance

Test Item	Test Spec.	Test Condition
Durability	a) no damage to interface b) meet the requirements of 5.1, and mating and unmating force requirement	After 500 mating cycles @ 12 cycles per minute
Center Contact Retention Force	4 pounds min. (axial)	
Mating Force	14 pounds max.	
Unmating Force	14 pounds max. 2 pounds min.	
Insertion Force (Center Contact)	2.5 pounds max.	
Withdrawal Force (Center Contact)	0.5 ounce min.	
Cable Retention Force Crimping	Cable O.D> Force min. <3.93 mm 5 lbs 3.94-4.80 mm 10 lbs 4.81-5.82 mm 20 lbs 5.83-6.33 mm 30 lbs >6.34 mm 40 lbs	
Non-crimping	40 lbs	

E	PER ECN 0942	Andy 961223	TITLE : GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS
D	PER ECN 0845	Audy 960716	
С	PER ECN 0778	20dana 960312	Product Specification
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
DOCUM	PS - 735	598-0104	Prepared By: R. Fudda Date: 941114 SHEET NO.
			Checked By (S/) Date a/ 7 4 of 10

Date : 76122 4 of Date: 761230

5.3 Environmental Performance

Test Item	Test Spec.	Test Condition
Corrosion (Salt Spray)	No exposure of the base metal on the interface or mating surface.	MIL-STD-202F,Method 101D. Test Condition B. (less RF leakage)
Moisture Resistance	a) Insulation Resistance should be at least 200 megohms b) Parts will be tested for insulation resistance	MIL-STD-202F, Method 106F, (Less Step 7a & b)
Thermal Shock	a) No major effects to operating or physical properties.b) I hour duration.	MIL-STD-202F, Method 107G, Test Condition A
Vibration(High Frequency)	a) No discontinuity greater than 1 m sec. b) Tolerance of vibration amplitude is +/- 10% c) Vibration frequency shall be varied logarithmically between 10 to 2,000 Hz. d) The entire frequency range of 10 to 2,000 Hz and return to 10 Hz shall be transgressed in 20 minutes.	MIL-STD-202F, Method 204D, Test condition B

E	PER ECN 0942	Andy 961223	TITLE : GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS	
D	PER ECN 0845	Audy 960716		
С	PER ECN 0778	200san 960312	Product Specification	
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
DOCUMENT NO PS - 73598-0104			Prepared By: R. Fulfs Date: 941114 SHEET NO. Checked By: Date: 961220 Approved By: Date: 761220	

Mechanical Shock -----

a) No discontinuity greater than 1 m.sec.

MIL-STD-202F, Method 213B, Test Condition A

b) An 11 m.sec. duration. c) 3 shocks in each direction.

E	PER ECN 0942	Andy 961223	TITLE: GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTORS		
D	PER ECN 0845	Andy 960716	75. 1		
С	PER ECN 0778	Welson 960312	Product Specification		
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
DOCUM	MENT NO		. Description of the Control of the		

PS - 73598-0104

Date:941114

Approved By: ∽

6 of 10

6.0 Test Sequence

All sample units shall be subjected to the inspection of group I. The samples shall then be divided into subgroups consisting of five each connectors. The sample units shall then be subjected to the inspection for their particular group.

GROUP I

Visual & Mechanical Examination (Material, Finish)

 \forall

Mating & Unmating Force

- ↓

Insulation Resistance

E	PER ECN 0942	Andy 961223	TITLE: GENERAL SPECIFICATION FOR SPECIAL 75 OHM SMB SERIES CONNECTOR	RS.		
D	PER ECN 0845	Andy 960716	D 1 2			
С	PER ECN 0778	Wilson 960312	Product Specification		Product Specification	
REV	DESCRIPTION	SIGN	THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
PS - 73598-0104				NO. f 10		





