

REVISIONS				DATE	APPROVED
2	REV	DESCRIPTION	DATE		
-		ORIGINAL RELEASE	2/7/03		

Description:

Low Noise Amplifier designed for Military and Industrial applications. This amplifier is supplied in our standard PE2 housing that can be used as a SMA connectorized or a surface mount component. Other packages and connector types are available.

This model provides the following performance. Data is available upon request.

Specifications:

Frequency Range: 0.25 to 18.0 GHz
Gain: 15dB Typ.
Gain Flatness: +/-1.5dB Max.
Noise Figure: 5.0dB Typ.
OP1dB: 13dBm Min.
VSWR Input/Output: 2.0:1 Max.
DC Voltage Supply: +12 to +15V/DC
DC Current Draw: 65mA Max.

Features:

Internal Voltage Regulation
Unconditional Stability
Standard Operating Temperature -20 to +70 Deg. C

Available Options:


Various Package types
Various Connector types
Temperature Compensation
Hermetic Sealing
Gain and Phase Matching
MIL-STD-883 Screening Available

Environmental Ratings:


Temperature: -20 to +70 Deg. C (Operating) ; -55 to +85 Deg C (Available)
Humidity: MIL-STD-202F, METHOD 103B COND B.
Shock: MIL-STD-202F, METHOD 213B COND B.
Altitude: MIL-STD-202F, METHOD 105C COND B.
Temperature Cycle: MIL-STD-202F, METHOD 107D COND A

Note: The above specifications are subject to change or revision.

PE2 HOUSING WITH CARRIER



PE2 HOUSING WITHOUT CARRIER (SURFACE MOUNT)



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
± .XX ± 0.010 ±
.XXX ± 0.005

PART NO.		DATE		TITLE		REV	
MATERIAL:		APPROVALS		DATE		REV	
6061-T6 Aluminum		K. Mason		2/27/03		1	
FINISH:		PRODUCT FEATURE		DATE		REV	
Gold Plating over Nickel		PE2-15-0R2518R0-5R0-15-12-SFF		B. 11K53		1	
DO NOT SCALE DRAWING		WEB - MODEL		A		1 OF 1	