



75 Ohm F Female Bulkhead Connector Crimp/
Solder Attachment For RG6-CATV

TECHNICAL DATA SHEET

PE44324

75 Ohm F Female Bulkhead Connector Crimp/Solder Attachment For RG6-CATV

Configuration

Connector	F Female
Connector Interface Type	RG6-CATV
Cable Attachment Method (Shield/Contact)	Crimp/Solder
Body Style	Straight
Mount Method	Bulkhead

Electrical Specifications

Frequency Range, MHz	DC to 1,000
Impedance, Ohms	75
Maximum VSWR	1.3:1
Maximum Operating Voltage, Volts	500
Dielectric Withstanding Voltage, Vrms	1,000

Mechanical Specifications

Temperature

Operating Range, deg C	-40 to +85
------------------------	------------

Size

Length, in [mm]	1.23 [31.24]
Width/Dia., in [mm]	0.438 [11]
Weight, lbs [g]	0.11 [49.9]

Connector

Type	F Female
Contact Material and Plating	Brass, Gold
Contact Plating Specification	30µ in. minimum
Body Material and Plating	Brass, Nickel
Body Plating Specification	100µ in. minimum
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm F Female Bulkhead Connector Crimp/Solder Attachment For RG6-CATV PE44324](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

75 Ohm F Female Bulkhead Connector Crimp/
Solder Attachment For RG6-CATV



TECHNICAL DATA SHEET

PE44324

75 Ohm F Female Bulkhead Connector Crimp/Solder Attachment For RG6-CATV from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm F Female Bulkhead Connector Crimp/Solder Attachment For RG6-CATV PE44324](http://www.pasternack.com/f-female-standard-rg6-catv-connector-pe44324-p.aspx)

URL: <http://www.pasternack.com/f-female-standard-rg6-catv-connector-pe44324-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE44324 CAD Drawing

75 Ohm F Female Bulkhead Connector Crimp/Solder Attachment For RG6-CATV



CRIMP SIZE REQUIRED
CONTACT: SOLDER
FERRULE: .314" HEX CRIMP TOOL

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

DWG TITLE
PE44324

P**ASTERNACK**[®]
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

REV. B	FSCM NO. 53919	CAD FILE 013012	SCALE N/A	SIZE A	2233
--------	----------------	-----------------	-----------	--------	------