




HASCO, INC
COMPONENTS DISTRIBUTOR

(888) 498-3242 • www.hasco-inc.com



HA141C Series

18 GHz - .141 Dia. Conformable Cable

FEATURES

- RoHs Compliant 
- Easily Hand-Formable to Final Shape
- Anti-torque Nut on SMA Straight Connectors
- 100% VSWR test to 18 GHz
- 100% Hi-pot and continuity tests
- Insertion Loss: +25°C: 0.4 dB + 0.065 x length (per inch)

ELECTRICAL SPECIFICATIONS

Max Frequency (GHz)	20
Capacitance (pF/Ft)	29
Velocity Propagation (%)	70
RF Leakage @ 18 GHz (dB)	>100
Time Delay (ns/Ft)	1.46
Impedance (Ohms)	50

MECHANICAL SPECIFICATIONS

Cable Max Dia. (Inch)	0.141
Min. bend radius (Inch)	0.25
Recommend Bend Radius (Inch)	1.5
Raw Cable Temperature Range (°C)	-55 to +200

MATERIALS AND FINISHES

DESCRIPTION	MATERIALS	FINISH OR COLOR
Marker	Mil-I-23053	Black
Contacts	Brass	Gold Plated
Insulators	PTFE	None
Connector Bodies	Brass	Gold
Connector Nuts	Stainless Steel	Passivated
Gasket	Silicon Rubber	A-A-59588

HOW TO ORDER: HA141C-XX-XX-L


***Example: HA141C-S1-S2-L
1 2A 2B 3

1. Cable Type
2. Connectors: (A&B) SMA Male (Plug) = S1
SMA Female (Jack) = S2
3. Length in Inches L = Inches



Typical performance @ +25° C

Insertion Loss vs. Frequency - 12 in. cable



VSWR vs. Frequency - 12 in. cable

