



2.4mm Female to Mini SMP Male Adapter Full Detent

TECHNICAL DATA SHEET

PE91122

2.4mm Female to Mini SMP Male Adapter Full Detent

Configuration

Connector 1 2.4mm Female
Impedance 1 50 Ohms
Connector Specification 1 MIL-STD-34B
Connector 2 Mini SMP Male
Impedance 2 50 Ohms
Adapter Design

Adapter Design Standard Body Style Straight

Electrical Specifications

Frequency Range, GHz DC to 50 Maximum VSWR 1.25:1

Mechanical Specifications

Temperature

Operating Range,deg C -55 to +125

Size

Length, in [mm] 0.917 [23.29] Width/Dia., in [mm] 0.25 [6.35]

Connector 1

Type 2.4mm Female Inner Conductor Material and Plating Beryllium Copper, Gold

Inner Conductor Plating Specification MIL-G-45204, Type 1, Grade C, Class 1
Outer Conductor Material and Plating Beryllium Copper, Gold

Outer Conductor Plating Specification

MIL-G-45204, Type 1, Grade C, Class 1

Body Material and Plating

Beryllium Copper, Gold

Beryllium Copper, Gold

Body Plating Specification MIL-G-45204, Type 1, Grade C, Class 1

Dielectric Type P

Connector 2

Type Mini SMP Male

Outer Conductor Material and Plating Passivated Stainless Steel

Outer Conductor Plating Specification AMS-QQ-P-35

Body Material and Plating Passivated Stainless Steel

Body Plating Specification AMS-QQ-P-35

Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Female to Mini SMP Male Adapter Full Detent PE91122

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





2.4mm Female to Mini SMP Male Adapter Full Detent

TECHNICAL DATA SHEET

PE91122

Plotted and Other Data

Notes:

Values at 25 °C, sea level

2.4mm Female to Mini SMP Male Adapter Full Detent from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Female to Mini SMP Male Adapter Full Detent PE91122

URL: http://www.pasternack.com/2.4mm-female-mini-smp-male-straight-adapter-pe91122-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE91122 CAD Drawing2.4mm Female to Mini SMP Male Adapter Full Detent

