


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 1.5–3.0 GHz
Coupling: 40 ± 1.25 dB
Frequency Sensitivity: ± 0.75 dB
Insertion Loss: 0.20 dB Max.
Directivity: 25 dB Min.
VSWR: 1.20:1 Max.
Power: 50W, 3kW Peak

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A	
DRAWN: Paiboon Luekhamhan		DATE: 01-17-1998		DRAWING TITLE: DIRECTIONAL COUPLER	
APPROVED: T. Nguyen		DATE: 01-17-1998		PART NO. C1-40	
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5	
		THIRD ANGLE PROJECTION		SIZE: A REV: N/A DO NOT SCALE THE DRAWING	
				DWG NO. 82082	