



SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

TECHNICAL DATA SHEET

PE44827

SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

Configuration

ConnectorSMA FemaleConnector SpecificationMIL-STD-348Connector Interface TypeThru HoleCable Attachment Method (Shield/Contact)SolderBody StyleStraight

Electrical Specifications

Impedance, Ohms 5

Mechanical Specifications

Size

Length, in [mm] 0.53 [13.46] Width/Dia., in [mm] 0.276 [7.01]

Connector

Type SMA Female

Contact Material and Plating Beryllium Copper, Gold

Outer Conductor Material and Plating Brass, Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes: Values at 25 °C, sea level

SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing PE44827

URL: http://www.pasternack.com/sma-female-standard-thru-hole-pcb-connector-pe44827-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44827 CAD Drawing

SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

